SSM SUSUMU
Thin Film Specialist and Innovator

英語版
English Version

Thin film surface mount resistors
Resistors with radial leads
Current sensing surface mount resistors
Power choke coils
High frequency surface mount components
Sample kits
Standard specification

Thin Film Products
Components
Complete Product Catalogue

SUSUMU CO., LTD.

On Environment

You are making "Ecologically Sound" decisions by using Susumu products!

- The Thin Film deposition process requires minimal amounts of raw materials.
  Thin Film resistors are manufactured by processes that utilize minimal amounts of raw materials.
- Our processes use less electricity and emit less CO2.
  Number of heating, curing and sintering process are minimized. When heat is required,
  We use temperature as low as possible.
- Our products are extremely small :using fewer of the earth's natural resources.
  Even though they are small, their precision performance is unmatched.
- Using Susumu's products means reducing your products' environmental load.
  By using Susumu's products, you are contributing to a healthy environment.

Susumu's thin film products are environmentally friendly.

- All Susumu's products are RoHS compliant.
- Almost all products are halogen-free correspondence products.

The following logos designate "greenness" of the products.

About REACH

REACH was established by the European Chemical Agency (ECHA) in 2007 in order to manage the risk that chemicals pose to health and the environment. REACH stands for

Registration, Evaluation, and Authorization of Chemicals.

174 Subsistences listed in SVHC. (Updated in Nov 2017)

Weight ratio (%) for each structural part of typical thin film chip resistors

Product series (Structural part)		RG1005	RG1608 URG1608	RG2012 URG2012	RG3216 URG3216	PRG3216	PRG6432	RM2012	RM3216	RoHS compliance *1
Ceramic substrate		83.18	86.95	87.63	89.51	89.36	92.26	87.78	92.86	●
Resistive element		0.02	0.02	0.02	0.02	0.02	0.11	0.02	0.02	●
Terminal: bottom layer		0.16	0.13	0.11	0.15	0.15	0.11	0.15	0.10	●
Terminal: middle layer		8.33	5.82	5.58	4.83	4.82	3.49	5.87	2.96	●
Terminal: outer layer		5.45	3.81	3.65	3.16	3.15	2.28	3.84	1.94	●
Protective coating	A									●
	B	2.87	2.93	2.67	2.06	2.22	1.79	1.99	1.88	●
	C									●
Marking ink			0.34	0.36	0.28	0.28	0.07	0.37	0.25	●
Total weight (mg)		0.72	2.07	4.12	8.26	8.27	30.81	4.11	7.96	●

*1 Contact our sales office regarding the composition of restricted or hazardous materials.

The long life of Susumu products means effective usage of natural resources.

■URG series P.11

■RG series P.15

The RG series, with its inorganic passivation, realizes less than +/-0.25% drift after 10000 hour stress tests. The ultra reliable URG series also uses inorganic passivation technology and attains less than +/-0.02% drift after similar stress tests.

Small sizes and high power handling capability also mean effective usage of natural resources.

■PRG series P.23

Size	Rated power (W)		Power ratio
	RG series	PRG series	
2012 / 2010	1/8	1/2	4 times
3216	1/4	1	4 times

■HRG series P.27

Size	Rated power (W)		Power ratio
	RG series	HRG series	
3216	1/4	1	4 times

Susumu, together with its group companies, is striving to manufacture environmentally friendly and high quality products.

Susumu group companies' ISO14001 certification status

Company names	facility location	Certification date	Authentication update date (revision date)	Certification body	Certification No.
Susumu Co. Ltd	Obama, Japan	2000.12.15	2015.12.15 (2017.11.17)	JQA	EM1184
	Kyoto Headquarters, and other sales offices				
	Niigata, Japan	2001.03.09	2016.03.09 (2018.02.23)	JQA	EM1388
Susumu(Suzhou) Co., Ltd.	Suzhou (China)	2015.09.23	—	BUREAU VERITAS	4815E20237ROM
Cyntec	Hsin-Chu (Taiwan)	2002.08.26		UL	A11463
	Suzhou (China)	2003.10.22		UL	A11463

Susumu group companies' ISO9001 certification status

Company names	facility location	Certification date	Authentication update date (revision date)	Certification body	Certification No.
Susumu Co. Ltd	Obama, Japan	1998.11.06	2018.03.14	JQA	JQA2755
	Kyoto Headquarters, and other sales offices				
	Niigata, Japan	1988.07.23	2015.08.08 (2017.09.20)	JQA	JQA-QM3580
Susumu(Suzhou) Co., Ltd.	Suzhou (China)	2011.05.01	2017.05.01	BUREAU VERITAS	CNBJ311009-UK
Cyntec	Hsin-Chu (Taiwan)	1997.03.06	2016.03.04	UL	A5443
	Suzhou (China)	1997.03.06	2016.03.04	UL	A5443

Susumu group companies' IATF 16949 certification status

Company names	facility location	Certification date	Authentication update date (revision date)	Certification body	Certification No.
Susumu Co. Ltd	Obama, Japan	2004.11.12	2018.02.21	JQA	JQA-AU0068 (IATF：0204847)
	Kyoto Headquarters, and other sales offices				
	Niigata, Japan	2015.10.01	2015.10.01 (2017.09.20)	JQA	JQA-AU0289 (IATF：0220148)
Susumu(Suzhou) Co., Ltd.	Suzhou (China)	2011.05.02	2017.02.09	BUREAU VERITAS	CHN-C-15072/TS (IATF：180043)
Cyntec	Hsin-Chu (Taiwan)	2007.04.24	2016.03.04	UL	49187
	Suzhou (China)	2007.04.24	2016.03.04	UL	65364

Table of Contents

Susumu and the Environment 01

Products list 03

Selection Guide 05

In order for customers to choose the best parts for their requirements, the following pages contain tables that provide an outline for each product series. For details, please refer to the specification pages or contact our sales office.

Table for E series resistant values; table for 3 letter designation of E96 resistive value 07

Handling care for our products. 08

Products specifications 10

Thin film surface mount resistors

Resistors with radial leads

Current sensing surface mount resistors

Power choke coils

High frequency surface mount components

Sample kits

Standard specification 96

International sales offices 111

Products categories

Product group	Product category	Series	Power ratings (W)														Resistance tolerance (%)							*2 Environmental compliance	Specification pages
			3	2	1.5	1	3/4	1/2	0.3	1/4	1/5	1/8	1/10	1/16	1/20	1/32	± 0.01	± 0.02	± 0.05	± 0.1	± 0.5	± 1	± 20		
Thin film surface mount resistors	Metal thin film chip resistors (the highest reliability and precision)	URG					●	●		●			●	●			●	●	●	●	●			●	11-14
	Metal thin firm chip resistors (the highest precision)	RG								●		●	●	●		●			●	●	●			●	15-16
	Metal thin firm chip resistors (wide temperature range)	RGT											●	●		●				●	●			●	17-18
	Non-magnetic thin film chip resistors	NRG								●		●	●						●	●	●			●	19-20
	Audio thin film chip resistors (high precision)	RS												●		●				●	●			●	21-22
	High power thin film chip resistors (long side terminal)	PRG	●	●	●	●														●	●			●	23-26
	High power thin film chip resistors (short side terminal)	HRG				●														●	●			●	27-28
	Anti-surge thin film chip resistors	MRG						●		●		●	●							●	●			●	29-30
	High temperature thin film chip resistors	RGA											●	●		●				●	●			●	31-32
	Metal thin film chip resistors (precision)	RR								●		●	●	●	●					●	●	●		●	33
	Metal thin film trimmable chip resistors	RT											●	●	●								●	●	34
	Metal thin film chip resistor networks	RM										●	●				●*1	●*1	●	●	●			●	35-42
	High temperature metal thin film resistor networks	RMA									●	●	●				●*1	●*1	●	●	●			●	43-44

Product group	Product category	Series	Power ratings (W)														Resistance tolerance (%)								*2 Environmental compliance	Specification pages
			3	2	1.5	1	3/4	1/2	0.3	1/4	1/5	1/8	1/10	1/16	1/20	1/32	±0.01	±0.02	±0.05	±0.1	±0.25	±0.5	±1	±20		
Resistors with radial leads	Radial lead metal thin film chip resistors (the highest reliability and precision)	LRG							●								●	●	●	●					●	47-48

Product group	Product category	Series	Power ratings (W)																Resistance tolerance (%)				*2 Environmental compliance	Specification pages
			10	8	6	5	4	3	2	1.5	1	3/4	2/3	1/2	1/3	1/4	1/5	1/6	1/8	±0.5	±1	±2	±5		
Current sensing surface mount resistors	Metal foil low resistance chip resistors (long-side terminal)	KRL	●		●	●	●	●	●	●	●			●							●	●	●	●	51-52
	Metal foil low resistance chip resistors (short-side terminal)	KRL				●			●	●		●		●	●	●			●		●	●	●	●	53-54
	Metal foil low resistance chip resistors (4 terminal type)	KRL		●		●	●	●	●		●										●	●	●	●	55-56
	Precision low resistance chip resistors	SHR												●						●				●	57-58
	Low resistance chip resistors (long-side terminal)	PRL/ RL							●		●		●		●					●	●	●	●	●*3	59-60
	Low resistance chip resistors (short-side terminal)	RL									●			●	●	●	●	●	●		●	●	●	●*3	61-62
	High Current chip jumpers	YJP																						●	63

Product group	Product category	Series	Inductance (μH)						Rated current (A)						*2 Environmental compliance	Specification pages
			0.1 ~ 0.49	0.5 ~ 0.99	1.0 ~ 2.9	3.0 ~ 4.9	5.0 ~ 9.9	10 ~	0.45 ~ 0.9	1.0 ~ 4.9	5.0 ~ 9.9	10 ~ 19.9	20.0 ~ 34.9	35.0 ~		
Power choke coils	Power choke coils	PCMB	●	●	●	●	●	●	●	●	●	●	●	●	●	67
	Small power choke coils	PCMB /PS	●	●	●	●	●	●	●	●	●	●			●	68

Product group	Product category	Series	Attenuation (dB)													Attenuation tolerance (dB)									*2 Environmental compliance	Specification pages
			0	1	2	3	4	5	6	7	8	9	10	16	20	±0.1	±0.2	±0.3	±0.4	±0.5	±0.7	±0.75	±0.8	±1.0		
High frequency surface mount components	Precision chip attenuators	PAT	●	●	●	●	●	●	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●	73-76
	Precision chip attenuators (W type)	PAT-W	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●	●	●					●	77-80
	Thermo-variable chip attenuators	P*V	●	●	●	●	●	●	●	●	●	●	●	●						●					●	81-84

Product group	Product category	Series	Input power ratings (mW)				Frequency range (DC ~ X GHz)				Power balance			*2 Environmental compliance	Specification pages
			500	250	125	100	20	17.5	15	10	0.3dB	0.5dB	1.0dB		
High frequency surface mount components	Chip power splitter	PS	●	●	●	●	●	●	●	●	●	●	●	●	85-86

Product group	Product category	Series	Power ratings (W)											Frequency range (DC ~ X GHz)					VSWR					*2 Environmental compliance	Specification pages
			100	60	30	20	10	5	2.5	2	1	0.5	0.2	15	12.5	10	7.5	5	3	1.2	1.3	1.4	1.5	1.6		
High frequency surface mount components	High power thin film chip terminator	PCS/ HPT	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	87-90

*1 Relative tolerance

*2 Environmental compliance: EU-RoHS, REACH SVHCxx, Completely Pb free, Halogen free

*3 RoHS compliant but resistive element contains few ppm level lead. Not completely lead free.

Selection Guide

The RG series, the most popular metal thin film chip resistors because of their high precision, high reliability and long-term stability, is the base of our line-up of new innovative products: a higher precision, higher operating temperature, higher power handling capability, higher anti-surge capability version of the RG series and so on.
All of these products employ the inorganic passivation technology that enables high precision and high reliability.
In addition, our thin film based terminal technology does not involve any Ag (silver) and they are sulfur impervious.
The following diagram shows distinctive characteristics of these products and their relationships.

Higher precision : URG series, LRG series (with radial leads)
Higher operating temperature : RGT series, RGA series, RMA series (resistive networks)
High power : PRG series (long side terminal), HRG series (short side terminal)
Anti-surge : MRG series
Non-magnetic : NRG series
Audio grade : RS series

Relation map of thin film chip resistors



Map from discreet RG series to resistor networks



Thin film resistor map by performance

Thin film resistors are highly reliable and stable over long periods of time. The diagrams below show the matrix of Susumu's thin film resistors based on tolerance with TCR , and tolerance with power ratings.
The high power resistors are offered in two different terminal configurations; PRG series -long side terminal and HRG series - short side terminal, to meet your need for miniaturization using same power.



Current sensing chip resistors' relation map

The diagram below illustrates how we expanded our current sensing chip resistors in order to meet the need for miniaturization and high power ratings.
We also offer 4 terminal current sensor isolating voltage terminals, making it easier to mount on the board.
We will continue to expand current sensing chip resistor series corresponding the needs of the market.



E series resistance values (IEC designated series of resistance values)

series	Values														
E-6	1.0		1.5		2.2		3.3		4.7		6.8				
E-12	1.0	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2			
E-24	1.0	1.1	1.2	1.3	1.5	1.6	1.8	2.0	2.2	2.4	2.7	3.0	3.3	3.6	3.9
	4.3	4.7	5.1	5.6	6.2	6.8	7.5	8.2	9.1						
E-96	1.00	1.02	1.05	1.07	1.10	1.13	1.15	1.18	1.21	1.24	1.27	1.30	1.33	1.37	1.40
	1.43	1.47	1.50	1.54	1.58	1.62	1.65	1.69	1.74	1.78	1.82	1.87	1.91	1.96	2.00
	2.05	2.10	2.15	2.21	2.26	2.32	2.37	2.43	2.49	2.55	2.61	2.67	2.74	2.80	2.87
	2.94	3.01	3.09	3.16	3.24	3.32	3.40	3.48	3.57	3.65	3.74	3.83	3.92	4.02	4.12
	4.22	4.32	4.42	4.53	4.64	4.75	4.87	4.99	5.11	5.23	5.36	5.49	5.62	5.76	5.90
	6.04	6.19	6.34	6.49	6.65	6.81	6.98	7.15	7.32	7.50	7.68	7.87	8.06	8.25	8.45
	8.66	8.87	9.09	9.31	9.53	9.76									

Three-letter codes for resistance value (Codes for Marking in E96 series)

(1) A manufacturing date code: Refer to JIS C 5201-1.
(2) Three digits of number shall be marked on the protective coating. In this case, the three digits of code number shall be added at the end of type designation.

(Example) 4.99KΩ = 499 × 10^1

Marking: 68H
Type designation: RR0816P-4991-D-68H

code	E96 value	code	E96 value	code	E96 value	code	E96 value	code	E96 value	code	E96 value	code	E96 value	code	E96 value
01	100*	13	133	25	178	37	237	49	316	61	422	73	562	85	750*
02	102	14	137	26	182	38	243	50	324	62	432	74	576	86	768
03	105	15	140	27	187	39	249	51	332	63	442	75	590	87	787
04	107	16	143	28	191	40	255	52	340	64	453	76	604	88	806
05	110*	17	147	29	196	41	261	53	348	65	464	77	619	89	825
06	113	18	150*	30	200*	42	267	54	357	66	475	78	634	90	845
07	115	19	154	31	205	43	274	55	365	67	487	79	649	91	866
08	118	20	158	32	210	44	280	56	374	68	499	80	665	92	887
09	121	21	162	33	215	45	287	57	383	69	511	81	681	93	909
10	124	22	165	34	221	46	294	58	392	70	523	82	698	94	931
11	127	23	169	35	226	47	301	59	402	71	536	83	715	95	953
12	130*	24	174	36	232	48	309	60	412	72	549	84	732	96	976

code for power of 10

code	power
A	10^0
H	10^1
C	10^2
D	10^3
E	10^4
F	10^5
R	10^{-1}
S	10^{-2}

* The resistance value duplicated in E24 series and in E96 series shall be manufactured in E24 series only.

Disclaimer and handling care of our products

Disclaimer

1. The contents of this catalogue are only for reference purposes and its contents may be changed without prior notification. Official specifications will be submitted to each customer. For ordering, please contact our sales representatives

2. The products listed in this catalogue are for general purpose electronic equipment. Please consult with us if you require specific qualities or reliability as in nuclear or aerospace applications.

3. When you incorporate our products in your design, please utilize them within their specified operating conditions such as rated power and recommended operating temperature. We cannot guarantee our products and cannot take responsibility for the failure of our products if they are used under improper conditions or outside of the parameters of our specified conditions.

4. No part of this publication may be reproduced by any means without the permission of Susumu Co. ltd.

Handling and care

< Consideration during mounting >

(1) Before, during and after mounting, take care not to damage the protective coating of the products. Damage to the protective coating may result in weakening the humidity tolerance.

(2) When using a soldering iron, the heat should be applied to the land pattern not directly to the component. The tip of the soldering iron should not touch the resistors directly. In addition, when the tip of the soldering iron is hot, please do soldering as quick as possible(Below 350℃ within 3 seconds).

(3) Flux residue can cause corrosion and electro-migration resulting in the deterioration of humidity tolerance. If you utilize highly activated flux, such as flux containing chlorine, please consult with us prior to usage.

(4) Ionized foreign material contamination or residue can also cause corrosion and electro-migration resulting in the deterioration of humidity tolerance. Do not touch the components with bare hands prior to or after mounting.

(5) If the soldering operation takes place at very high temperatures and for a prolonged period of time, the terminal may dissolve into the solder.

(6) When mounted components are embedded into resin or polymer, the resin/polymer selection must consider heat tolerance, humidity tolerance, mechanical properties, and chemical or ion composition.

< Operating environment; condition >

(1) If these components are utilized for unusual conditions, the reliability and characteristics should be verified in advance. Such conditions include:

① Exposure of the component to water, salt water, oils, acids, alkaline, or solvents

② Exposure of the component to direct sunlight, outdoor weather conditions, or heavy dust

③ Exposure to frost

④ Possible exposure to corrosive air or gas such as a marine atmosphere, HCl, Cl_2, H_2S, NH_3, SO_2, and NOx.

(2) Usage under high temperatures and high humidity

① When components are used under high temperature conditions, assess the potential temperatures surrounding the components considering the other heat-producing neighboring components, and regulate your power usage following the specified derating curve.

② If the components are used under high humidity conditions or at temperatures below the dew point, the products can experience positive resistance drift or even an open circuit.

(3) Use our products under the rated power when the pulse current or voltage is applied. The peak voltage of the pulse should remain under the rated voltage.

MEMO

Thin film surface mount resistors

Metal thin film chip resistors
(the highest reliability and precision)
URG series

Metal thin firm chip resistors
(the highest precision)
RG series

Metal thin film chip resistors
(wide temperature range)
RGT series

Non-magnetic metal thin film chip resistors
NRG series

Audio thin film chip resistors
(high precision)
RS series

High power thin film chip resistors
(long side terminal)
PRG series

High power thin film chip resistors
(short side terminal)
HRG series

Anti-surge thin film chip resistors
MRG series

High temperature thin film chip resistors
RGA series

Metal thin film chip resistors
(precision)
RR series

Metal thin film trimmable chip resistors
RT series

Metal thin film chip resistor networks
RM series

High temperature metal thin film resistor networks
RMA series

Lead free　Halogen free　RoHS Compliance

Metal thin film chip resistors
(the highest reliability and precision)

■URG series　　**AEC-Q200 Compliant**

Features

- The tightest resistance tolerance: +/-0.01%
- The smallest temperature coefficient of resistance: ±1ppm/℃
- Long term stability with inorganic passivation
- Thin film structure enabling low noise and anti-sulfur

Applications

- Industrial measurement, electrical scales
- High precision sensors, medical electronics

◆Part numbering system

URG 2012 L - 102 - L - T1

- URG: Series code
- 2012: Size: URG1608, URG2012, URG3216, URG5025, URG6432
- L: Temperature coefficient of resistance
- 102: Nominal resistance value (E-24: 3 digit, E-96: 4 digit, URG3216, URG5025, URG6432: all 4 digit)
- L: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T05(500pcs), T01(100pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance *1 (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.01% (L)	±0.02% (P)	±0.05% (W)	±0.1% (B)	±0.5% (D)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
URG1608	1/16W	±1(K)	100≦R≦7.5k					100V	E24, E96	-55℃ ~ 155℃	T1
		±2(L)									
URG2012	1/10W	±1(K)	100≦R≦36k					150V			T05
		±2(L)									
URG3216	1/4W	±1(K)	100≦R≦68k					200V			T01
		±2(L)									
URG5025	1/2W	±1(K)	100≦R≦150k					300V			T01
		±2(L)									
URG6432	3/4W	±1(K)	100≦R≦200k					300V			
		±2(L)									

*1 Applicable TCR range -20°C ~ 125°C

***Contact us for requirements not listed in above table.**

◆Dimensions



Type	Size (inch)	L	W	a	t
URG1608	0603	1.60±0.20	0.80+0.25/−0.20	0.30±0.20	0.40+0.15/−0.10
URG2012	0805	2.00±0.20	1.25+0.25/−0.20	0.40±0.20	0.40+0.15/−0.10
URG3216	1206	3.20±0.20	1.60±0.25	0.50±0.25	0.40+0.15/−0.10
URG5025	2010	5.00±0.20	2.50±0.25	0.60±0.25	0.45+0.15/-0.10
URG6432	2512	6.40+0.20/−0.40	3.20±0.25	0.75±0.25	0.45±0.20

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±0.02%+0.01Ω
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 2000hours	±0.02%+0.01Ω(R≧250Ω)
		±0.05%+0.01Ω(R<250Ω)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±0.05%+0.01Ω
Temperature shock	-65℃ (15min) ~ 150℃ (15min) 100cycles	±0.02%+0.01Ω
High temperature exposure	155℃, no bias, 1000hours	±0.05%+0.01Ω
Resistance to soldering heat	235±5℃, 30 seconds (reflow), (by MIL-PRF-55342)	±0.01%+0.01Ω

*1 Rated voltage is given by E= $\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

Metal thin film chip resistors
(the highest reliability and precision)

■URG series

◆Reliability test data

○Biased life test





○High temperature high humidity (biased)





○Temperature shock





○High temperature exposure





◆Temperature coefficient of Resistance

○URG2012





○URG3216





◆Derating Curve



Metal thin film chip resistors
(the highest precision)

■RG series **AEC-Q200 Compliant**

Lead free　Halogen free　RoHS Compliance

Features

- Long term stability with inorganic passivation
- Less than ±0.1% drift after 10000 hors of reliability test
- High precision resistance tolerance: ±0.05%, very small TCR: ±5ppm/℃
- Thin film structure enabling low noise and anti-sulfur

Applications

- Automotive electronics
- Industrial measurement instrumentation, industrial machines
- Various sensors, medical electronics

◆Part numbering system

RG 1608 N - 102 - B - T5

- RG: Series code
- 1608: Size: RG1005, RG1608, RG2012, RG3216
- N: Temperature coefficient of resistance
- 102: Nominal resistance value (E-24: 3 digit, E-96: 4 digit, RG3216: all 4 digit)
- B: Resistance tolerance
- T5: Packaging quantity: T5(5,000pcs), T10(10,000pcs)

◆Electrical Specification

Type	Power ratings			Temperature coefficient of resistance	Resistance range (Ω) Resistance tolerance (%)				Maximum voltage	Resistance value series	Operating temperature	Pakaging quantity
	Low	Regular	High	(ppm/°C)	±0.02% (P)	±0.05% (W)	±0.1% (B)	±0.5%(D)				
RG1005	1/32W	1/16W	1/8W	±5(V)	100≦R<3k				75V	E-24, E-96	-55℃ ~ 155℃	T5 T10
				±10(N)	100≦R<3k	47≦R<100k						
				±25(P)	100≦R<3k	47≦R<100k		47≦R<150k				
				±100(R)	—	—	—	10≦R<47				
RG1608	1/16W	1/10W	1/6W	±5(V)	100≦R<5.1k				100V			T5
				±10(N)	100≦R<5.1k	47≦R≦270k						
				±25(P)	100≦R<5.1k	47≦R≦270k	47≦R≦332k	47≦R≦1M				
				±50(Q)	—	—	—	10≦R<47				
RG2012	1/10W	1/8W	1/4W	±5(V)	100≦R<10.2k				150V			
				±10(N)	100≦R<10.2k	47≦R≦475k						
				±25(P)	100≦R<10.2k	47≦R≦475k	47≦R≦2.7M					
				±50(Q)	—	—	—	10≦R<47				
RG3216	1/8W	1/4W	—	±5(V)	100≦R<33.2k				200V			
				±10(N)	100≦R<33.2k	47≦R≦1M						
				±25(P)	100≦R<33.2k	47≦R≦1M	47≦R≦5.1M					
				±50(Q)	—	—	—	10≦R<47				

◆Dimensions



Type	Size (inch)	L	W	a	b	t
RG1005	0402	1.00+0.1/−0.05	0.50±0.05	0.20±0.10	0.25±0.05	0.35±0.05
RG1608	0603	1.60±0.20	0.80±0.20	0.30±0.20	0.30±0.20	0.40±0.10
RG2012	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.40±0.10
RG3216	1206	3.20±0.20	1.60±0.20	0.50±0.25	0.50±0.20	0.40±0.10

(unit : mm)

◆Reliability specification

Test Items	Condition (test methods)	Low		Regular		High		Typical
		≦47Ω	≧47Ω	≦47Ω	≧47Ω	≦47Ω	≧47Ω	Low
Short time overload	2.5 x rated voltage,*1 5 seconds	±0.10%	±0.05%	±0.10%	±0.05%	—	±0.10%	±(0.01%)
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 1000hours	±0.25%	±0.10%	±0.50%	±0.25%	—	±0.50%	±(0.01%)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±0.25%	±0.10%	±0.50%	±0.25%	—	±0.50%	±(0.05%)
Temperature shock	-55℃ (30min) ~ 125℃ (30min) 1000cycles	±0.25%	±0.10%	±0.25%	±0.10%	—	±0.10%	±(0.01%)
High temperature exposure	155℃, no bias, 1000hours	±0.25%	±0.10%	±0.25%	±0.10%	—	±0.10%	±(0.01%)
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±0.1%	±0.1%	±0.1%	±0.1%	—	±0.1%	±(0.01%)

*1 Rated voltage is given by E= $\sqrt{R \times P}$ E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆10000 hour reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



○High temperature exposure



◆Derating Curve



◆Maximum pulse power limit



Test procedure

Voltage pulse is applied to the test samples mounted on the test board.
After each pulse, resistance drift is measured. Pulse voltage is increased until the drift exceeds +/-0.5%. The power at that voltage is defined as the maximum pulse power.

Metal thin film chip resistors
(wide temperature range)

■RGT series **AEC-Q200 Compliant**

Features

- Wide temperature operation (Upper category temperature :175°C)
- Long term stability with igorganic passivation
- Resistance tolerance : ±0.1% , TCR : ±10ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Automotive electronics
- Industrial measurement instrumentation, industrial machines
- Wide temperature operation machines

◆Part numbering system

RGT 2012 N - 105 - B - T5

- RGT — Series code
- 2012 — Size: RGT1005, RGT1608, RGT2012
- N — Temperature coefficient of resistance
- 105 — Nominal resistance value (E-24 : 3 digit, E-96 : 4 digit)
- B — Resistance tolerance
- T5 — Packaging quantity : T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance		Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
		(ppm/℃)	±0.1%(B)	±0.5%(D)				
RGT1005	1/32W	±10(N)	10≦R≦100k		50V	E-24, E-96	-55℃~ 175℃	T5
		±25(P)	10≦R≦150k					
RGT1608	1/16W	±10(N)	10≦R≦270k		100V			
		±25(P)	10≦R≦1M					
RGT2012	1/10W	±10(N)	10≦R≦475k		150V			
		±25(P)	10≦R≦2.7M					

◆Dimensions



Type	Size (inch)	L	W	a	b	t
RGT1005	0402	1.00+0.1/-0.05	0.50±0.05	0.20±0.10	0.25±0.05	0.35±0.05
RGT1608	0603	1.60±0.20	0.80±0.20	0.30±0.20	0.30±0.20	0.40±0.10
RGT2012	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.40±0.10

(unit : mm)

◆Reliability specification

Test items	Condition(IEC60115-1/JIS C5201-1)	Standard	
		<47Ω	≧47Ω
Short time overload	2.5 x rated voltage,※1 5 seconds	±0.05%	
Life (baised)	125℃, rated voltage※1, 90min. ON/ 30min. OFF, 1000hours	±0.5%	±0.25%
High temperature high humidity	85℃、85%RH, 1/10 of rated power, 90min. ON/ 30min. OFF, 1000hours	±0.5%	±0.25%
Temperature shock	-55℃ (30min) ~ 125℃(30min) 1000 cycles	±0.25%	±0.1%
High temperature exposure	175℃, no baias, not mounted, 1000h	±0.25%	±0.1%

*1 Rated voltage is given by E= $\sqrt{R \times P}$ E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

◯Biased life test



◯High temperature exposure



◆Derating Curve



Non-magnetic metal thin film chip resistors

■NRG series

Features

- Thin film chip resistors using non-magnetic materials
- Long term stability with inorganic passivation
- High precision resistance tolerance: ±0.05%, very small TCR: ±5ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Medical electronics, industrial measurement instrumentation
- equipment/devises under magnetic field

◆Part numbering system

NRG 2012 V - 104 - W - T1

- NRG: Series code
- 2012: Size: NRG1608, NRG2012, NRG3216
- V: Temperature coefficient of resistance
- 104: Nominal resistance value (E-24: 3 digit, E-96: 4 digit, NRG6432: all 4 digit)
- W: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance			Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
		(ppm/°C)	±0.05% (W)	±0.1%(B)	±0.5%(D)				
NRG1608	1/10W	±5(V)	100≦R<5.1k			100V	E-24,E-96	-55℃ ~155℃	T1 T5
		±10(N)	47≦R≦270k						
		±25(P)	47≦R≦270k	47≦R≦332k	47≦R≦360k				
		±50(Q)	—	—	10≦R<47				
NRG2012	1/8W	±5(V)	100≦R<10.2k			150V			
		±10(N)	47≦R≦475k						
		±25(P)	47≦R≦475k	47≦R≦1M					
		±50(Q)	—	—	10≦R<47				
NRG3216	1/4W	±5(V)	100≦R<33.2k			200V			
		±10(N)	47≦R≦1M						
		±25(P)	47≦R≦1M						
		±50(Q)	—	—	10≦R<47				

◆Dimensions



Type	Size (inch)	L	W	a	t
NRG1608	0603	1.60±0.20	0.80+0.25/−0.20	0.30±0.20	0.40+0.15/−0.10
NRG2012	0805	2.00±0.20	1.25+0.25/−0.20	0.40±0.20	0.40+0.15/−0.10
NRG3216	1206	3.20±0.20	1.60±0.25	0.50±0.25	0.40+0.15/−0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±0.5%
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 2000hours	±0.5%
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 2000hours	±0.5%
Temperature shock	-65℃ (30min) ~ 150℃ (30min) 100cycles	±0.5%
High temperature exposure	155℃, no bias, 1000hours	±0.5%
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±0.05%

*1 Rated voltage is given by $E=\sqrt{R \times P}$ E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



◆Derating Curve



Audio thin film chip resistors
(high precision)

■RS series **AEC-Q200 Compliant**

Lead free Halogen free RoHS Compliance

Features

- Improved low noise thin film character even further
- Choice among the same resistance/size according to the user's sound preference
- Precision resistance tolerance: ±0.1%, very small TCR: ±25ppm/°C

Applications

- High quality audio equipment
- Automotive audio equipment
- Mobile audio equipment , smartphones

◆Part numbering system

RS 1005P - 102 - B - T10 - 3

- RS: Series code
- 1005: Size
- P: Temperature coefficient of resistance
- 102: Nominal resistance value
- B: Resistance tolerance
- T10: Packaging quantity: T5(5,000pcs), T10(10,000pcs)
- 3: Please contact our sales office for details.

◆Electrical Specification

Type	Power ratings		Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance		Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
	Low	Regular	(ppm/°C)	±0.1%(B)	±0.5%(D)				
RS1005	1/32W	1/16W	±25(P)	47≦R≦100K		75V	E-6	-55℃ ~ 155℃	T5 T10
RS2012	1/10W	1/8W	±25(P)	47≦R≦100K		150V			T5

* Please contact our sales office for details.

◆Dimensions



Type	Size (inch)	L	W	a	b	t
RS1005	0402	1.00+0.10/-0.05	0.50±0.10	0.20±0.10	0.25±0.05	0.35±0.05
RS2012	0805	2.00±0.20	1.25+0.25/-0.20	0.40±0.20	0.40±0.20	0.40+0.15/-0.10

(unit : mm)

◆Derating Curve



High power thin film chip resistors
(long side terminal)

■PRG series **AEC-Q200 Compliant**

Lead free Halogen free RoHS Compliance

Features

- Long side terminal enabling higher power capability
- Significantly larger power handling capability than conventional same size resistors
  Size: 2010 ~ 6432, power ratings: 0.5 ~ 3.0W, Resistance range: 2.5 ~ 250KΩ
- Precision resistance tolerance: ±0.1%, very small TCR: ±25ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Automotive electronics
- DC motor, inverters
- Robotics, Industrial control system

◆Part numbering system

PRG 3216 P - 1001 - B - T5

- PRG: Series code
- 3216: Size: PRG2010, PRG3216 PRG5020, PRG6432
- P: Temperature coefficient of resistance
- 1001: Nominal resistance value (E-24, E-96: all 4 digit)
- B: Resistance tolerance
- T5: Packaging quantity: T4(4,000pcs) (PRG6432, PRG5020) T5(5,000pcs) (PRG3216, PRG2010)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance		Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
		(ppm/°C)	±0.1% (B)	±0.5% (D)				
PRG2010	0.5W	±25(P)	47≦R≦25k	10≦R≦25k	100V	E-24, E-96	-55℃ ~ 155℃	T5
		±50(Q)		2.5≦R≦25k				
PRG3216	1.0W	±25(P)	47≦R≦100k	10≦R≦100k	150V			
		±50(Q)		2.5≦R≦100k				
PRG5020	1.5W ~ 2.0W	±25(P)	47≦R≦200k	10≦R≦200k	200V			T4
		±50(Q)		2.5≦R≦200k				
PRG6432	2.0W ~ 3.0W	±25(P)	47≦R≦250k	10≦R≦250k	400V			
		±50(Q)		2.5≦R≦250k				

◆Dimensions



Type	Size (inch)	L	W	a	b	t
PRG2010	0804	2.00±0.20	1.00±0.20	0.20±0.10	0.25±0.05	0.35±0.05
PRG3216	1206	3.20+0.40/-0.20	1.60±0.20	0.30±0.20	0.35±0.20	0.45+0.15/-0.10
PRG5020	2008	5.00±0.20	2.00±0.20	0.40±0.20	0.40±0.20	0.45+0.15/-0.10
PRG6432	2512	6.40+0.20/-0.40	3.20±0.25	0.45±0.20	0.55±0.20	0.45+0.15/-0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (JIS C5201-1)	Standard	
		≦47Ω	≧47Ω
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 1000hours	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
Temperature shock	-55℃ (30min) ~ 125℃ (30min) 1000cycles	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
High temperature exposure	155℃, no bias, 1000hours	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±(0.1%+0.01Ω)	±(0.05%+0.01Ω)

*1 Rated voltage is given by $E=\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

High power thin film chip resistors
(long side terminal)

■PRG series

◆Reliability test data

○Biased life test







○High temperature high humidity (biased)









◯Temperature shock









◯High temperature exposure









◆Derating Curve

◯PRG3216



◯PRG6432



High power thin film chip resistors
(short side terminal)

■HRG series **AEC-Q200 Compliant**

Lead free Halogen free RoHS Compliance

Features

- Wider bottom terminal enabling higher power capability (short side terminal)
- Significantly larger power handling capability than existing same size resistors
  Size: 3216, Power rating: 1.0W, Resistance range: 10 ~ 100KΩ
- Precision resistance tolerance: ±0.1%, very small TCR: ±25ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Power source related devises
- DC motors, inverters
- Robotics, Industrial control system

◆Part numbering system

HRG 3216 P - 1001 - B - T5

- HRG: Series code
- 3216: Size: HRG3216
- P: Temperature coefficient of resistance
- 1001: Nominal resistance value (E-24, E-96: all 4 digit)
- B: Resistance tolerance
- T5: Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance		Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
		(ppm/°C)	±0.1% (B)	±0.5% (D)				
HRG3216	1.0W	±25(P)	47≦R≦100k		200V	E-24, E-96	-55℃ ~ 155℃	T1 T5
		±50(Q)	47≦R≦100k	10≦R≦100k				

◆Dimensions



Type	Size (inch)	L	W	a	b	t
HRG3216	1206	3.20±0.20	1.60±0.25	0.50±0.25	1.10±0.20	0.40+0.15/−0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (JIS C5201-1)	Standard	
		≦47Ω	≧47Ω
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 1000hours	±(0.5%+0.05Ω)	±(0.25%+0.01Ω)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
Temperature shock	-55℃ (30min) ~ 125℃ (30min) 1000cycles	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
High temperature exposure	155℃, no bias, 1000hours	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±(0.25%+0.05Ω)	±(0.1%+0.01Ω)

*1 Rated voltage is given by $E=\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



○High temperature exposure



◆Derating Curve



Anti-surge thin film chip resistors

■MRG series

AEC-Q200 Compliant

Features

- Significant improvement of anti-surge capability comparing to existing thin film resistors
- Precision resistance tolerance: ±0.1%, very small TCR: ±10ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Power source related devices
- Automotive electronics
- Robotics, Industrial control system

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

MRG 2012 N - 104 - B - T5

- MRG — Series code
- 2012 — Size: MRG2012, MRG3216, MRG5025
- N — Temperature coefficient of resistance
- 104 — Nominal resistance value (E-24, E-96, MRG3216: all 4 digit)
- B — Resistance tolerance
- T5 — Packaging quantity: T5(5,000pcs) (MRG2012, MRG3216) T4(4,000pcs) (MRG5025)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.1% (B)	±0.5% (D)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
MRG2012	1/10W	±10(N)	100≦R≦1M		150V	E-24, E-96	-55℃ ~ 155℃	T5
		±25(P)						
MRG3216	1/8W	±10(N)	100≦R≦2M		200V			
		±25(P)						
MRG5025	1/2W	±10(N)	100≦R≦2M		300V			T4
		±25(P)						

◆Dimensions



Type	Size (inch)	L	W	a	t
MRG2012	0805	2.00±0.20	1.25+0.25/−0.20	0.40±0.20	0.40+0.15/−0.10
MRG3216	1206	3.20±0.20	1.60±0.25	0.50±0.25	0.40+0.15/−0.10
MRG5025	2010	5.00±0.20	2.50±0.25	0.60±0.25	0.45+0.15/−0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±0.05%
Life (biased)	85℃, rated voltage,*1 90min on 30min off, 2000hours	±0.25%
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 2000hours	±0.25%
Temperature shock	-55℃ (30min) ~ 125℃ (30min) 2000cycles	±0.1%
High temperature exposure	155℃, no bias, 2000hours	±0.5%
ESD (HBM)	4KV (Positive 3times, negative 3 times)	±0.5%
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±0.1%

*1 Rated voltage is given by $E=\sqrt{R \times P}$ E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



○High temperature exposure



◆Derating Curve



◆Maximum pulse power limit (single pulse)



◆Maximum pulse power limit (multiple pulses)





Lead free Halogen free RoHS Compliance

High temperature thin film chip resistors

■RGA series

AEC-Q200 Compliant

Features

- Conductive epoxy compatible
- Operating temperature up to 230°C
- Resistance tolerance: ±0.1%, TCR: ±10ppm/°C
- Thin film structure enabling low noise and anti-sulfur

Applications

- Automotive electronics
- Equipment used in high temperature
- Downhole drilling

◆Part numbering system

RGA 2012 N - 104 - B - T1

- RGA — Series code
- 2012 — Size: RGA1005, RGA1608,RGA2012
- N — Temperature coefficient of resistance
- 104 — Nominal resistance value (E-24: 3digit, E-96: 4digit)
- B — Resistance tolerance
- T1 — Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.1% (B)	Resistance range(Ω) Resistance tolerance ±0.5% (D)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
RGA1005	1/32W	±10(N)	47≦R≦100k		50V	E-24, E-96	-55℃ ~ 230℃	T1 T5
		±25(P)	10≦R≦100k					
RGA1608	1/16W	±10(N)	47≦R≦274k		100V			
		±25(P)	10≦R≦332k	10≦R≦360k				
RGA2012	1/10W	±10(N)	47≦R≦475k		150V			
		±25(P)	10≦R≦1M					

◆Dimensions



Type	Size (inch)	L	W	a	t
RGA1005	0402	1.00+0.1/-0.05	0.50±0.10	0.20±0.10	0.35±0.05
RGA1608	0603	1.60±0.20	0.80+0.25/−0.20	0.30±0.20	0.40+0.15/−0.10
RGA2012	0805	2.00±0.20	1.25+0.25/−0.20	0.40±0.20	0.40+0.15/−0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±(0.1%+0.01Ω)
Life (biased)	125℃, rated voltage,*1 90min on 30min off, 1000hours	±(0.2%+0.05Ω)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±(0.2%+0.01Ω)
Temperature shock	-55℃ (30min) ~ 125℃ (30min) 1000cycles	±(0.2%+0.01Ω)
High temperature exposure	155℃, no bias, 1000hours	±(0.2%+0.05Ω)
Vibration	Frequency 10Hz ~ 500Hz, vibration amplitude 1.5mm or acceleration 10gn test duration for each of 3 axis: 6 hours	±(0.2%+0.05Ω)
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±(0.5%+0.01Ω)

*1 Rated voltage is given by E=$\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



○High temperature exposure



◆Derating Curve



Metal thin film chip resistors (precision)

■RR series

Features

· Precision chip resistors excellent in resistance tolerance, TCR, frequency performance, noise characteristics, and linearity.

Applications

· Consumer electronics that requires precision resistors
· All purpose resistors in any area of electronics

◆Part numbering system

RR 0816 P - 102 - D - (M) - (T5) - (***)

- RR — Series code
- 0816 — Size: RR0306, RR0510, RR0816, RR1220, RR1632, RR2632,
- P — Temperature coefficient of resistance
- 102 — Nominal Resistance value: RR0306, RR0510, RR0816, RR1220 E-24: 3 digit, E-96: 4 digit; RR1632, RR2632: 4 digit
- D — Resistance tolerance
- (M) — Letter M is added for RR1220 E-96 series 4digit codes
- (T5) — Taping quantity: RR1632, RR2632 5000pcs:T5; RR0306, RR0510, RR0816, RR1220: nocode is given
- (***) — only given to 3 digit coders for RR0816 E-96 series

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.1% (B)	±0.5% (D)	±1% (F)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
RR0306	1/20W	±25(P)	33≦R≦22k			15V	E-24	-55℃ ~ 125℃	5,000pcs
		±100(R)	–	–	10≦R≦30				
RR0510	1/16W	±25(P)	–	100≦R≦100k	–	25V	E-24, E-96		10,000pcs
		±100(R)		10≦R<100					
RR0816	1/16W	±25(P)	–	100≦R≦360k	–	75V			5,000pcs
		±50(Q)		10≦R<100					
RR1220	1/10W	±25(P)	–	100≦R≦1M		100V			
		±50(Q)	–	10≦R<100	–				
RR1632	1/8W	±5(V)	100≦R≦200k	–	–	150V			T5
		±10(N)							
		±25(P)		51≦R≦1M	–				
		±50(Q)	–	10≦R≦49.9					
RR2632	1/4W	±5(V)	100≦R≦330k	–	–	200V			
		±10(N)							
		±25(P)		51≦R≦2M	–				
		±50(Q)	–	10≦R≦49.9					

◆Dimensions



Type	Size (inch)	L	W	a	b	t
RR0306	0201	0.60±0.05	0.30±0.05	0.12±0.05	0.12±0.05	0.23±0.03
RR0510	0402	1.00±0.05	0.50±0.05	0.20±0.10	0.25±0.05	0.35±0.05
RR0816	0603	1.60±0.20	0.80±0.20	0.30±0.20	0.30±0.20	0.40±0.10
RR1220	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.40±0.10
RR1632	1206	3.20±0.20	1.60±0.20	0.50±0.20	0.45±0.20	0.40±0.10
RR2632	1210	3.20±0.20	2.60±0.20	0.50±0.20	0.45±0.20	0.40±0.10

(unit : mm)



Metal thin film trimmable chip resistors

■RT series

AEC-Q200 Compliant

Lead free　Halogen free　RoHS Compliance

Features

- Patented trimming method (Patent# 1921853)guarantees precision trimming, post trimming stability and short trimming time.
- Available as small as 0.3mm x 0.6mm

Applications

- Sensor circuits that require accuracy (e.g. automotive electronics)
- PA module of mobile phone
- Devices that requires anti-vibration stability (e.g. microphone)

◆Part numbering system

RT 0816 P - 102 - M

- RT: Series code
- 0816: Size: RT0603, RT0510, RT0816, RT1220
- P: Temperature coefficient of resistance
- 102: Nominal resistance value
- M: Resistance tolerance

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Initial resistance value (Ω) Targetted resistance value (Ω)				Initial resisstance value tolerance (%)	Maximum voltage	Operating temperature	Packaging quantity
RT0603	1/20W	±25(P)	150	330	-	-	±20(M)	15V	-55℃ ~ 125℃	15,000pcs
			1.0k	1.9k	-	-				
		±100(R)	1.5k	-	-	-				
			10k	-	-	-				
RT0510	1/16W	±25(P)	100	270	-	-		25V		10,000pcs
			820	2.1k	-	-				
		±100(R)	1.5k	-	-	-				
			10k	-	-	-				
RT0816	1/16W	±25(P)	100	330	1.0k	-		75V		5,000pcs
			2.7k	8.0k	8.8k	-				
		±100(R)	-	3.3k	10k	--				
			-	37k	40k	-				
RT1220	1/10W	±25(P)	100	330	1.0k	-		100V		5,000pcs
			8.2k	15k	15k	-				
		±50(Q)	33	-	-	-				
			4.7k	-	-	-				
		±100(R)	3.3k	10k	33k	100k				
			100k	120k	120k	220k				

◆Dimensions



Type	Size (inch)	L	W	a	b	t
RT0603	0201	0.60±0.05	0.30±0.03	0.12±0.05	0.15±0.05	0.25±0.03
RT0510	0402	1.00±0.07	0.50±0.07	0.20±0.10	0.25±0.20	0.35±0.05
RT0816	0603	1.60±0.20	0.80±0.20	0.30±0.20	0.30±0.20	0.40±0.10
RT1220	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.40±0.10

(unit : mm)

Lead free　Halogen free　RoHS Compliance

Metal thin film chip resistor networks

■RM series

AEC-Q200 Compliant

Features

- Relative resistance tolerance and relative TCR definable among multiple resistors within package.
- Relative resistance tolerance: ±0.01%, relative TCR: ±1ppm/°C
- Number of resistors in package: 2 or higher, standard and custom circuits designs available
- RG series equivalent reliability and long term stability: less than ±0.1% drift after 10000 hour stress test.
- RoHS compliant, 100% lead free

Applications

- Precision measurement instrumentation, medical electronics, automotive electronics
- Voltage divider and amplification circuits that require very precise relative resistance tolerance and TCR
- Multi step precision amplification circuits for minute signals

◆Part numbering system

RM 2012 A - */*** - P W X L 10**

- RM: Series code
- 2012: Size: RM2012, RM3216, RM3225
- A: circuits
- ***/***: Nominal Resistance Value(R1/R2)
- P: Absolute TCR
- W: Absolute resistance tolerance
- X: Relative TCR
- L: Relative resistance tolerance
- 10: Packaging quantity: 10(1,000pcs), 50(5,000pcs)

RM 3216 C - * - 10**

- RM: Series code
- 3216: Size: RM3216, RM3225, RM6432
- C: circuits
- ***: Custom part number (e.g.)N10
- 10: Packaging quantity: 10(1,000pcs), 50(5,000pcs)

※ **Please contact our sales office regarding custom products including resistance, resistance combination, number of elements, circuit, and others.**

※ **Standard quantity / reel is 1000 and 5000. Please contact our sales office for custom product's quantity / reel.**

※ **Standard resistance value pairings are shown as below**
(Standard products are 2element circuit typeA & typeB only.)

◆Standard resistance value pairings

Ratio	R1 (Ω)	R2 (Ω)	Ratio	R1 (Ω)	R2 (Ω)	Ratio	R1 (Ω)	R2 (Ω)	Ratio	R1 (Ω)	R2 (Ω)	Ratio	R1 (Ω)	R2 (Ω)	Ratio	R1 (Ω)	R2 (Ω)
1 : 1	1k	1k	1 : 3	1k	3k	1 : 5	1k	5k	1 : 9	1k	9k	1 : 20	1k	20k	1 : 50	1K	50k
	10k	10k		10k	30k		2k	10k		10k	90k		2k	40k		2K	100k
	100k	100k		100k	300k		10k	50k	1 : 10	1k	10k		5k	100k	1 : 100	1K	100k
1 : 2	1k	2k	1 : 4	1k	4k	1 : 6	1k	6k		2k	20k	1 : 25	1k	25k		2K	200k
	10k	20k		10k	40k		10k	60k		10k	100k		2k	50k			
	100k	200k															

◆Electrical Specification

○ 4 terminal, 2 element

Top view, terminal number	Circuit diagram (circuit type A)
	

Top view, terminal number	Circuit diagram (circuit type B)
	

Type	Power ratings (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)*1				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance*2			Absolute tolerance	Relative tolerance*2			
				Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500		Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500	
RM2012	0.05W / Element 0.1W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3216	0.083W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 500k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3225	0.1W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 500k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

*1 TCR guaranteed range : -20°C~ 125°C
*2 Contact us for detailed information on relative tolerance and TCR.

○ 4 terminal, 3 element

Top view, terminal number	Circuit diagram (circuit type C)	Circuit diagram (circuit type D)	Circuit diagram (circuit type E)
			

○ 6 terminal, 3 element

Top view, terminal number	Circuit diagram (circuit type H)
	

Type	Power rating (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)*1				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance*2			Absolute tolerance	Relative tolerance*2			
				Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500		Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500	
RM3216	0.042W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3225	0.066W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

*1 TCR guaranteed range : -20°C ~ 125°C
*2 Contact us for detailed information on relative tolerance and TCR.

Metal thin film chip resistor networks

■RM series

○ 6 terminal, 4 element



Type	Power ratings (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)*1				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance*2			Absolute tolerance	Relative tolerance*2			
				Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500		Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500	
RM3216	0.032W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3225	0.05W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

*1 TCR guaranteed range : -20°C ~ 125°C
*2 Contact us for detailed information on relative tolerance and TCR.

○ 8 terminal, 4 element



Type	Power ratings (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)*1				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance*2			Absolute tolerance	Relative tolerance*2			
				Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500		Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500	
RM3216	0.032W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3225	0.05W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM6432	0.1W / Element 0.4W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 40=4,000pcs
		300 ~ 1M	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

*1 TCR guaranteed range : -20°C ~ 125°C
*2 Contact us for detailed information on relative tolerance and TCR.

◯ 8 terminal, 6 element

Top view, terminal number	Circuit diagram (circuit type G)
	

Type	Power ratings (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)*1				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance*2			Absolute tolerance	Relative tolerance*2			
				Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500		Resistance ratio =1	1< Resistance ratio ≦100	100< Resistance ratio ≦500	
RM3216	0.021W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM3225	0.033W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RM6432	0.066W / Element 0.4W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 1M	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

*1 TCR guaranteed range : -20°C ~ 125°C
*2 Contact us for detailed information on relative tolerance and TCR.

◯ Some examples of custom RM series

RM2525(2.5mm×2.5mm)

Top view, terminal number	Circuit diagram (e.g.)
	

RM5882(5.8mm×8.2mm)

Top view, terminal number	Circuit diagram (e.g.)
	

RM10280(10.2mm×7.2mm)

Top view, terminal number	Circuit diagram (e.g.)
	

RM8258(8.2mm×5.8mm)

Top view, terminal number	Circuit diagram (e.g.)
	

RM11264(11.2mm×6.4mm)

Top view, terminal number	Circuit diagram (e.g.)
	

RM5050(5.0mm×5.0mm)

Top view, terminal number	Circuit diagram (e.g.)
	

Metal thin film chip resistor networks

■RM series

◆Dimensions



4 terminal

Type	Size (inch)	L	W	t	a	b	W1	W2
RM2012	0805	2.00±0.20	1.25±0.20	0.45±0.10	0.50±0.20	0.60±0.20	0.40±0.20	0.35±0.20
RM3216	1206	3.20±0.20	1.60±0.20	0.45±0.10	1.00±0.25	1.00±0.20	0.40±0.25	0.40±0.20
RM3225	1209	3.20±0.20	2.50±0.20	0.45±0.10	1.00±0.25	1.00±0.20	0.40±0.25	0.60±0.20

(unit : mm)



6 terminal

Type	Size (inch)	L	W	t	a1	a2	b1	b2	p1	p2	W1	W2
RM3216	1206	3.20±0.20	1.60±0.20	0.45±0.10	0.50±0.20	0.45±0.20	0.50±0.20	0.45±0.20	0.63±0.20	0.95±0.10	0.23±0.20	0.40±0.20
RM3225	1209	3.20±0.20	2.50±0.20	0.45±0.10	0.50±0.10	0.45±0.10	0.50±0.10	0.45±0.10	0.63±0.20	0.95±0.10	0.30±0.20	0.50±0.20

(unit : mm)



8 terminal

Type	Size (inch)	L	W	t	a1	a2	b1	b2	p1	p2	W1	W2
RM3216	1206	3.20±0.20	1.60±0.20	0.45±0.10	0.50±0.20	0.40±0.20	0.50±0.20	0.45±0.20	0.40±0.20	0.80±0.10	0.30±0.20	0.40±0.20
RM3225	1209	3.20±0.20	2.50±0.20	0.45±0.10	0.40 +0.20/-0.10	0.40 +0.10/-0.20	0.40 +0.10/-0.20	0.40 +0.10/-0.20	0.40±0.20	0.80±0.10	0.30±0.20	0.40±0.20
RM6432	2512	6.40±0.20	3.20±0.20	0.50±0.10	0.66 +0.20/-0.10	0.94 +0.10/-0.20	0.66 +0.20/-0.10	0.94 +0.10/-0.20	0.80±0.20	1.60±0.10	0.50±0.20	0.60±0.10

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard	
		Absolute tolerance	Relative tolerance
Short time overload	2.5 x rated voltage,*1 5seconds	±(0.05%+0.01Ω)	±0.02%
Life (biased)	85℃, rated voltage,*1 90min on 30min off, 1000hours	±(0.05%+0.01Ω)	±0.02%
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±(0.05%+0.01Ω)	±0.02%
Temperature shock	-55℃ (38min) ~ 125℃ (30min) 1000cycles*2	±(0.05%+0.01Ω)	±0.02%
High temperature exposure	155℃, no bias, 100hours	±(0.05%+0.01Ω)	±0.02%
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±(0.05%+0.01Ω)	±0.02%

*1 Rated voltage is given by $E=\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

*2 Based on the tests done on RM316.RM3225.
Please contact our sales office for other or custom dimensional products

Metal thin film chip resistor networks

■RM series

◆Reliability test data

○Load life with rated power @85°C





○High temperature high humidity (biased)





○Temperature shock





○High temperature exposure (155°C)





◆TCR linearity









◆Derating Curve





High temperature metal thin film resistor networks

■RMA series

AEC-Q200 Compliant

Lead free　Halogen free　RoHS Compliance

Features

- Conductive epoxy compatible chip resistor network
- Relative resistance tolerance: ±0.01%, relative TCR: ±1ppm/°C
- Operating temperature up to 230°C
- RoHS compliant, 100% lead free (gold terminal)
- Thin film structure enabling low noise and anti-sulfur

Applications

- Automotive electronics
- High temperature electronic devices
- Downhole drilling

◆Part numbering system

RMA 2012 A - */*** P B V L 10**

- RMA: Series code
- 2012: Size: RMA2012, RMA3216, RMA3225
- A: circuits
- ***/***: Nominal resistance value (E-24: 3 digit, E-96: all 4 digit)
- P: Absolute TCR
- B: Absolute resistance tolerance
- V: Relative TCR
- L: Relative resistance tolerance
- 10: Packaging quantity: 10(1,000pcs), 50(5,000pcs)

◆Electrical Specification

Top view, terminal number　Circuit diagram (circuit type A)



Top view, terminal number　Circuit diagram (circuit type B)



Type	Power ratings (85°C)	Resistance range (Ω)	Resistance tolerance (Code)				Temperature coefficient of resistance (Code)				Pakaging quantity (designation)
			Absolute tolerance	Relative tolerance			Absolute tolerance	Relative tolerance			
				Resistance ratio =1	1<Resistance ratio ≦100	100<Resistance ratio ≦500		Resistance ratio =1	1<Resistance ratio ≦100	100<Resistance ratio ≦500	
RMA2012	0.05W / Element 0.1W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	tape & reel (T&R) 10=1,000pcs 50=5,000pcs
		300 ~ 100k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RMA3216	0.063W / Element 0.125W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 500k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	
RMA3225	0.1W / Element 0.2W / Package	100 ~<300	±0.1%(B) ±0.5%(D)	±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.05%(W) ±0.1%(B) ±0.5%(D)	-	±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	-	
		300 ~ 500k	±0.05%(W) ±0.1%(B) ±0.5%(D)	±0.01%(L) ±0.02%(P) ±0.05%(W) ±0.1%(B) ±0.5%(D)		±0.05%(W) ±0.1%(B) ±0.5%(D)	±5ppm/℃(V) ±10ppm/℃(N) ±25ppm/℃(P)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±1ppm/℃(X) ±2ppm/℃(W) ±5ppm/℃(V)	±2ppm/℃(W) ±5ppm/℃(V)	

◆Dimensions



Type	Size (inch)	L	W	t	a	b	W1	W2
RMA2012	0805	2.0±0.2	1.25±0.2	0.45±0.1	0.5±0.2	0.6±0.2	0.4±0.2	0.35±0.2
RMA3216	1206	3.2±0.2	1.6±0.2	0.45±0.1	1.0±0.25	1.0±0.2	0.4±0.25	0.4±0.2
RMA3225	1209	3.2±0.2	2.5±0.2	0.45±0.1	1.0±0.25	1.0±0.2	0.4±0.25	0.6±0.2

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard	
		absolute	relative
Short time overload	2.5 x rated voltage*1, 5seconds	±(0.1%+0.01Ω)	±0.05%
Life (biased)	70℃, rated voltage, 90min on 30min off, 1000hours	±(0.1%+0.01Ω)	±0.05%
Temperature shock	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±(0.1%+0.01Ω)	±0.05%
High temperature exposure *2	-55℃ (30min) ~ 125℃ (30min)	±(0.1%+0.01Ω)	±0.05%
Resistance to soldering heat	155℃, no bias, 1000hours	±(0.1%+0.01Ω)	±0.05%

*1 Rated voltage is given by $E=\sqrt{R \times P}$ E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.
*2 Please contact our sales office for details.

◆Reliability test data

○Biased life test



○High temperature high humidity (biased)



○Temperature shock



◆Derating Curve



MEMO

Resistors with radial leads

Radial lead metal thin film chip resistors

(the highest reliability and precision)

LRG series

Radial lead metal thin film chip resistors(the highest reliability and precision)

■LRG series

Features

- Most reliable and the highest precision radial read thin film resistor
- The tightest resistance tolerance: +/-0.01%,the smallest temperature coefficient of resistance: ±1ppm/°C

Applications

- Industrial measurement, electrical scales
- High precision sensors, medical electronics

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

LRG 020 L - 1002 - L - T01

- LRG: Series code
- 020: Size
- L: Temperature coefficient of resistance
- 1002: Nominal resistance value
- L: Resistance tolerance
- T01: Packaging quantity: T01(100pcs)

◆Electrical Specification

Type	Lead pitch (mm)	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.01% (L)	±0.02% (P)	±0.05% (W)	±0.5% (D)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
LRG020	5.08	0.3W	±1(K)	100≦R≦100k				250V	E-24, E-96	-55℃ ~ 125℃	100pcs
			±2(L)								
			±5(V)								

◆Dimensions



◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±0.05%+0.01Ω
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 2000hours	±0.05%+0.01Ω
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 2000hours	±0.05%+0.01Ω
Temperature shock	-65℃ (15min) ~ 150℃ (15min) 100cycles	±0.05%+0.01Ω
High temperature exposure	155℃, no bias, 1000hours	±0.05%+0.01Ω
Resistance to soldering heat	260±5℃, 10 seconds (reflow)	±0.05%+0.01Ω

*1 Rated voltage is given by $E=\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

◆Reliability test data

○Biased life test



◆Derating Curve



MEMO

Current sensing surface mount resistors

Metal foil low resistance chip resistors
(long-side terminal)
KRL series

Metal foil low resistance chip resistors
(short-side terminal)
KRL series

Metal foil low resistance chip resistors
(4 terminal type)
KRL series

Precision low resistance chipresistors
SHR series

Low resistance chip resistors
(long-side terminal)
PRL / RL series

Low resistance chip resistors
(short-side terminal)
RL series

High Current chip jumpers
YJP series

Metal foil low resistance chip resistors
(long-side terminal)

■KRL series **AEC-Q200 Compliant**

Lead free | Halogen free | RoHS Compliance

Features

- High current sensing long side terminal low resistance chip resistor
- Two types available: high temperature (operating temperature up to 175°C), low emf type (operating temperature up to 155°C)
- High current handling capability and wide range of power ratings
- Size: 1608 ~ 15075, power ratings: 0.5W ~ 10W, resistance value range: 1m ~ 500mΩ
- Face down construction. Choice between bottom only or wrap around terminal.

Applications

- Automotive electronics
- Power source devises, ACDC converters, DCDC converters
- Motors, inverters, office automation equipment

◆Part numbering system

KRL 2012E - C - R010 - F - T1

- KRL: Series code
- 2012: Size: KRL1608, KRL2012, KRL3216, KRL5025 KRL6432, KRL7638, KRL9045, KRL11050 KRL15075
- E: Terminal type: D (bottom terminal), E (wrap around terminal)
- C: Temperature characteristics type: C (high operating temperature), M (low EMF)
- R010: Nominal resistance value
- F: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance *1			Resistance value series	Operating temperature		Packaging quantity
		(ppm/°C)	±1% (F)	±2% (G)	±5% (J)		C	M	
KRL1608	0.5W	±50	10m≦R≦100m	—	—	E-6 *2	-55℃ ~ 175℃	-55℃ ~ 155℃	T5
		±100	—	5m≦R≦9m	—				
KRL2012	1W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				T1 T5
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL3216	1.5W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL5025	2W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL6432	3W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL7638	4W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL9045	5W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL11050	6W	±50	3m≦R≦9m (1m step) 10m≦R≦500m	—	—				T1
		±100	—	R=2m	—				
		±150	—	—	R=1m				
KRL15075	10W	±50	10m≦R≦500m	—	—				
		±100	3m≦R≦9m (1m step)	R=2m	R=1m				
		±150	—	—	—				

*1 We can meet your requirement of less than 1mΩ. Please contact our sales office.
*2 We can meet your requirement of resistance value outside of E-6 series. Please contact our sales office.

◆Dimensions



D Type



E Type

Type	Size (inch)	L	W	t	a
KRL1608[*1]	0603	0.80±0.20	1.60±0.20	0.50±0.20	0.25±0.20(5mΩ~)
KRL2012	0805	1.25±0.20	2.00±0.20	0.50±0.20	0.30±0.20(2mΩ~)/0.55±0.20(1mΩ)
KRL3216	1206	1.60±0.20	3.20±0.20	0.50±0.20	0.30±0.20(2mΩ~)/0.55±0.20(1mΩ)
KRL5025	2010	2.50±0.20	5.00±0.20	0.50±0.20	0.40±0.20(2mΩ~)/0.55±0.20(1mΩ)
KRL6432	2512	3.10±0.20	6.30±0.20	0.50±0.20	0.50±0.20(2mΩ~)/1.20±0.20(1mΩ)
KRL7638	3015	3.80±0.20	7.60±0.20	0.50±0.20	0.60±0.20(2mΩ~)/1.35±0.20(1mΩ)
KRL9045	3518	4.50±0.20	9.00±0.20	0.50±0.20	0.70±0.20(2mΩ~)/1.60±0.20(1mΩ)
KRL11050	4320	5.00±0.20	11.00±0.20	0.50±0.20	0.80±0.20(2mΩ~)/1.60±0.20(1mΩ)
KRL15075	5930	7.50±0.20	15.00±0.20	0.65±0.20	1.10±0.20(1mΩ~)/2.75±0.20(0.5mΩ)

*1 KRL1608 dosen't have E Type

(unit : mm)

◆Derating Curve



Metal foil low resistance chip resistors
(short-side terminal)

■KRL series **AEC-Q200 Compliant**

Lead free Halogen free RoHS Compliance

Features

- High current sensing short side terminal low resistance chip resistor
- Two types available: high temperature (operating temperature up to 175°C), low emf type (operating temperature up to 155°C).
- High current handling capability and wide range of power ratings
- Size: 0510 ~ 50110, power ratings: 0.2W ~ 5W, resistance value range: 5m ~ 1000mΩ
- Face down construction. Choice between bottom only or wrap around terminal

Applications

- Automotive electronics
- Power source devises, ACDC converters, DCDC converters
- Motors, inverters, office automation equipment

◆Part numbering system

KRL 1220E - C - R010 - F - T1

- KRL: Series code
- 1220: Size: KRL0510, KRL0816, KRL1220, KRL1632 KRL2550, KRL3264, KRL50110
- E: Terminal type: D (bottom terminal), E (wrap around terminal)
- C: Temperature characteristics type: C (high operating temperature), M (low EMF)
- R010: Nominal resistance value
- F: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) *1 Resistance tolerance		Resistance value series	Operating temperature		Packaging quantity
		(ppm/°C)	±1% (F)	±2% (G)		C	M	
KRL0510	0.2W	±50	50m≦R≦100m		E-6 / E-12 *2	-55℃ ~ 175℃	-55℃ ~ 155℃	10,000pcs
		±100						
KRL0816	0.3W	±50	10m≦R≦500m	—				T1 T5
		±100	—	5m≦R≦9m(1m step)				
KRL1220	0.5W	±50	10m≦R≦500m	—				
		±100	—	5m≦R≦9m(1m step)				
KRL1632	0.75W	±50	10m≦R≦500m	—				
		±100	—	5m≦R≦9m(1m step)				
KRL2550	1.5W	±50	10m≦R≦500m	—				
		±100	—	5m≦R≦9m(1m step)				
KRL3264	2W	±50	10m≦R≦1000m	—				
		±100	—	5m≦R≦9m(1m step)				
KRL50110	5W	±50	10m≦R≦1000m	—				T1
		±100	—	5m≦R≦9m(1m step)				

*1 We can meet your requirement for resistance value not specified in above table. Please contact our sales office.
*2 We can meet your requirement outside of E-6/E-12 series resistance. Please contact our sales office.

◆Dimensions



D Type



E Type

Type	Size (inch)	L	W	t	a
KRL0510	0402	1.00±0.20	0.50±0.20	0.40±0.20	0.30±0.20
KRL0816	0603	1.60±0.20	0.80±0.20	0.50±0.20	0.30±0.20
KRL1220	0805	2.00±0.20	1.25±0.20	0.50±0.20	0.40±0.20
KRL1632	1206	3.20±0.20	1.60±0.20	0.50±0.20	0.40±0.20(9mΩ~)/1.10±0.20(5 ~ 8mΩ)
KRL2550	2010	5.00±0.20	2.50±0.20	0.50±0.20	0.60±0.20(9mΩ~ /1.40±0.20(5 ~ 8mΩ)
KRL3264	2512	6.30±0.20	3.10±0.20	0.50±0.20	1.00±0.20(9mΩ~)/1.90±0.20(5 ~ 8mΩ)
KRL50110	4320	11.00±0.20	5.00±0.20	0.65±0.20	2.36±0.20(8mΩ~)/3.60±0.20(5 ~ 7mΩ)

(unit : mm)

◆Derating Curve



KRL1632E-3A series (1W) and KRL3264E-3F series (3W) are also in our line-up.



Metal foil low resistance chip resistors
(4 terminal type)

■KRL series **AEC-Q200 Compliant**

Lead free Halogen free RoHS Compliance

Features

- Separated voltage terminal for precise measurement of voltage
- TCR stable at very low resistance: 4mΩ: ±50ppm/°C
- Power ratings: 1W ~ 5W

Applications

- Smartphones, mobile telephones, PCs, HDD, audio visual equipment, power devices, inverters.
- automotive electronics, industrial measurement instrumentation/equipment.

◆Part numbering system

KRL 3216T4 - M - R010 - F - T1
(KRL 3216T4A - M - R010 - F - T1)

- Series code
- Size: KRL3216T4, KRL6432T4, KRL7638T4 KRL9045T4, KRL11050T4,
- Temperature characteristics type: M (low EMF)
- Nominal resistance value
- Resistance tolerance
- Packaging quantity: T1(1,000pcs), T5(5,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) *1 Resistance tolerance			Resistance value series	Operating temperature	Packaging quantity
		(ppm/°C)	±1% (F)	±2% (G)	±5% (J)			
KRL3216T4 (KRL3216T4A)	1W	±50 (±35)	4m≦R≦9m (1m step) 10m≦R≦100m R=200m, 500m	—	—	E6 *2	-55℃ ~ 155℃ (Code M)	T1 T5
		±100 (±75)	R=3m	R=2m	R=1m			
KRL6432T4	2W	±50	4m≦R≦9m (1m step) 10m≦R≦100m R=200m, 500m	—	—			
		±100	R=3m	R=2m	R=1m			
KRL7638T4	3W	±50	4m≦R≦9m (1m step) 10m≦R≦100m R=200m, 500m	—	—			
		±100	R=3m	R=2m	R=1m			
KRL9045T4	4W	±50	4m≦R≦9m (1m step) 10m≦R≦100m R=200m, 500m	—	—			
		±100	R=3m	R=2m	R=1m			
KRL11050T4	5W	±50	4m≦R≦9m (1m step) 10m≦R≦100m R=200m, 500m	—	—			T1
		±100	R=3m	R=2m	R=1m			

*1 We can meet your requirement of less than 1mΩ. Please contact our sales office.
*2 We can meet your requirement of resistance value outside of E-6 series. Please contact our sales office.

◆Dimensions



Type	Size (inch)	L	W	a	b	c	d	t
KRL3216T4	1206	1.60±0.20	3.20±0.20	0.35±0.20	0.35±0.15	0.20±0.10	2.65±0.15	0.50±0.20
KRL6432T4	2512	3.20±0.20	6.40±0.20	0.50±0.20	0.70±0.15	0.50±0.10	5.20±0.15	0.50±0.20
KRL7638T4	3015	3.80±0.20	7.60±0.20	0.55±0.20	0.80±0.20	0.60±0.20	6.20±0.10	0.50±0.20
KRL9045T4	3518	4.50±0.20	9.00±0.20	0.50±0.20	0.70±0.20	0.50±0.20	5.20±0.10	0.50±0.20
KRL11050T4	4320	5.00±0.20	11.0±0.20	0.70±0.20	1.40±0.20	1.10±0.20	8.50±0.10	0.50±0.20

(unit : mm)

◆Circuit diagram



◆Derating Curve





Precision low resistance chip resistors

■SHR series

Features

- Precision with separated voltage terminal (4 terminals)
- Resistance tolerance: ±0.5%
- Resistance error with self heating: ±100ppm (0.1w ~ 0.5w)

Applications

- Electronic scales, test equipment, measuring equipment

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

SHR 6432 V - 3R0 - D - T1

- SHR: Series code
- 6432: Size: SHR6432
- V: Temperature coefficient of resistance
- 3R0: Nominal resistance value
- D: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T4(4,000pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance *1	Resistance range(Ω) *2 *3　Resistance tolerance *2	Operating temperature	Packaging quantity
		(ppm/°C)	±0.5% (D)		
SHR6432	0.5W	±5(V)	3≦R≦8	0℃ ~ 60℃	T1 T4

Information on above specification

*1	Coefficient of resistance by self heating	Resistance value, once powered, is influenced by the self-heating obtained by the following formula. *1 above is a designed value {R(P2) - R(P1)}/R(P1) * 100000 ≦ ±100ppm R(P1) : measured resistance value at 0.1w(25°C) R(P2) : measured resistance value at 0.5w(25°C)
*2	Resistance value range	Resistance value is obtained by the following formula. R=V/I　I=Vs/Rs Vs : Voltage applied to the standard resistor Rs : Standard resistance value V:1V (voltage at the time of resistance measurement)
*3	User resistance value	Please contact us for the resistance value you require.

◆Dimensions



Type	Size (inch)	L	W	t	a1	a2	w
SHR6432V	2512	6.4+0.2/-0.4	3.2±0.2	0.5±0.1	1.0+0.2/-0.1	4.2±0.2	0.55±0.2

(unit : mm)

◆Temperature characteristics



Low resistance chip resistors
(long-side terminal)

■PRL / RL series

Features

・Innovative structure that takes consideration of heat dissipation suppresses the surface temperature enabling the small sizes, reduction of the influence on surrounding components, excellent temperature cycle resistance, low ESL and low noise.

Applications

・PC power sources, inverters, automotive electronics, adopters, industrial machines

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

PRL 1220 - R010 - D - T5

- T5(5,000pcs): Packaging quantity
- D: Resistance tolerance
- R010: Nominal resistance value
- 1220: Size: PRL0816, PRL1220, PRL1632, PRL3264
- PRL: Series code

RL 3720W T - R10 - F

- F: Temperature coefficient of resistance
- R10: Resistance tolerance
- T: Nominal resistance value
- 3720W: Size: RL3720W, RL7520W
- RL: Series code

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±0.5% (D)	±1% (F)	±2% (G)	±5% (J)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
PRL0816	1/3W	±50	75m≦R≦100m		–	–	√(P・R)	E-24	-55℃ ~ 125℃	T5
		±100	43m≦R≦68m							
			–	33m≦R≦39m						
		0～+200	–	18m≦R≦27m						
		0～+350	–	10m≦R≦15m						
PRL1220	2/3W	±50	56m≦R≦100m			–		E-24 1m step (7m ~ 10m)		
		±100	47m≦R≦51m							
			–	20m≦R≦43m						
		0～+200	–	10m≦R≦18m						
		0～+350		–	7m≦R≦9m					
PRL1632	1W	±50	56m≦R≦100m			–		E-24 1m step (5m ~ 10m)		
		±100	20m≦R≦51m							
		0～+200	10m≦R≦18m							
		0～+350	–	5m≦R≦9m						
PRL3264	2W	±50	56m≦R≦100m			–		E-24 1m step (3m ~ 10m)		
			47m≦R≦51m							
		±100	–	20m≦R≦43m						
		0～+200	–	10m≦R≦18m						
		0～+350	–	5m≦R≦9m		3m≦R≦4m				
RL3720W	1W	±50(Q) ±100(R)	–	100m≦R≦1		–		E-24 1m step (1m ~ 10m)		4,000pcs
		0～+200(S)	–	5m≦R≦91m						
		0～+350(T)	–	1m≦R≦4m						
RL7520W	2W	±50(Q) ±100(R)	–	100m≦R≦470m		–		E-24 1m step (1m ~ 10m)		
				10m≦R≦91m						
		0～+200(S)	–	100m≦R≦470m						
		0～+350(T)	–	10m≦R≦91m						
		0～+420(T)	–	5m≦R≦9m						
		0～+800(T)	–	1m≦R≦4m						

◆Dimensions



Type	Size (inch)	L	W	a	b	t
PRL0816	0603	0.80±0.20	1.60±0.20	–	0.20±0.10	0.40±0.10
PRL1220	0805	1.25±0.20	2.00±0.20	–	0.35±0.15	0.50±0.10
PRL1632	1206	1.60±0.20	3.20±0.20	–	0.45±0.15	0.50±0.10
PRL3264	2512	3.20±0.20	6.40±0.20	–	0.90±0.15	0.50±0.10
RL3720W	1508	2.00±0.20	3.75±0.30	0.40±0.20	0.40+0.20	0.50±0.20
RL7520W	3008	2.00±0.20	7.50±0.30	0.40±0.20	0.40±0.20	0.50±0.20

(unit : mm)

◆ESL (Equivalent series inductance)



◆Surface temperature data

○ The high power type land pattern and surface temperature

These high-power low resistance chip resistors are designed to dissipate heat efficiently through the land patterns on circuit boards. The actual temperature of the surface of the resistor is dependent upon the dimensions and the shape of the land patterns.









◆Derating Curve



RL3720W



RL7520W

◆Resistance to power pulse



Test procedure

Voltage pulse is applied to the test samples mounted on the test board.
After each pulse, resistance drift is measured. Pulse vol tage is increased until the drift exceeds +/-0.5%.
The power at that voltage is defined as the maximum pulse power.

Low resistance chip resistors
(short-side terminal)

■RL series

Features

・Innovative structure that takes consideration of heat dissipation suppress the surface temperature enabling the small sizes reducing the influence of heat on surrounding components.

Applications

・PC power sources, inverters, automotive electronics, adopters, industrial machines

Lead free *1 | Halogen free | RoHS Compliance

*1 : Except for RL0510, RL1632 and RL3264

◆Part numbering system

RL 1220 S - 1R0 - F

- F: Resistance tolerance
- 1R0: Nominal resistance Value 1R0=1.0Ω
- S: Temperature coefficient of resistance
- 1220: Size : RL0510, RL0816, RL1220
- RL: Series code

RL 1632 S - R047 - F - T5

- T5: Packing quantity : T1 (1,000pcs), T5 (5,000pcs)
- F: Resistance tolerance
- R047: Nominal resistance Value 4digit
- S: Temperature coefficient of resistance
- 1632: Size : RL1632, RL3264
- RL: Series code

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance ±1% (F)	±2% (G)	±5% (J)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
RL0510	1/8W	0～+350(T)	50m≦R<100m			√(P・R)	E-24	-55℃ ~ 125℃	10,000pcs
	1/6W	0～+200(S)	100m≦R≦4.7		–				
			5.1≦R≦47						
RL0816	1/4W	0～+200(S)	20m≦R<100m						5,000pcs
		0～+350(T)							
	1/5W	0～+100(R)	100m≦R≦6.8	–					
		0～+200(S)	7.5≦R≦68						
RL1220	1/4W	0～+200(S)	43m≦R≦91m						
		0～+350(T)	10m≦R≦39m						
	1/3W	0～+100(R)	100m≦R≦10						
		0～+200(S)	11≦R≦100						
RL1632	1/2W	0～+100(R)	510m≦R≦4.7*1	56m≦R≦470m	–				T1 T5
		0～+200(S)	–	33m≦R≦51m					
		0～+350(T)		27m≦R≦30m	18m≦R≦24m				
		0～+500(T)		–	10m≦R≦16m				
RL3264	1W	0～+100(R)	–	56m≦R≦470m	–				
		0～+200(S)		33m≦R≦47m					
		0～+350(T)		27m	18m≦R≦22m				
		0～+500(T)		–	10m≦R≦15m				

*1 RL series with resistance tolerance 0.5% is also available. Please contact our sales office.

◆Dimensions



Type		Size (inch)	L	W	a	b	t
RL0510	R≦0.2Ω	0402	1.00±0.05	0.50±0.05	0.15±0.10	0.25±0.10	0.35+0.15/−0.10
	R>0.2Ω					0.15±0.10	0.35±0.10
RL0816	R≦0.082Ω	0603	1.60±0.20	0.80±0.20	0.20±0.15	0.25±0.20	0.45+0.15/−0.10
	R>0.091Ω					0.20±0.15	0.45±0.10
RL1220	R≦0.068Ω	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.50±0.20
	R>0.075Ω						0.40±0.10
RL1632		1206	3.20±0.20	1.60±0.20	—	1.00±0.15	0.50±0.15
RL3264		2512	6.40±0.20	3.20±0.20	—	2.00±0.15	0.50±0.15

(unit : mm)

◆Derating Curve



◆Resistance to power pulse



Test procedure

Voltage pulse is applied to the test samples mounted on the test board.
After each pulse, resistance drift is measured. Pulse voltage is increased until the drift exceeds +/-0.5%. The power at that voltage is defined as the maximum pulse power.

High Current chip jumpers

■YJP series

Features

- Simplify power line change, looping and circuit design when changing current
- Less than 0.3mΩ within operating temperature range
- Surface mount type eliminating jumper leads
- Help reduce the voltage drop/current loss in high current circuit
- Highly stable within operating temperature (-40~125°C)
- Halogen free

Lead free　Halogen free　RoHS Compliance

Applications

- Mobile phones, smart phones, automotive electronics, power sources, servers, PCs, etc.

◆Part numbering system

YJP 1608 - R001

- YJP — Series code
- 1608 — Size : YJP1608, YJP3216
- R001 — Maximum resistor value

◆Electrical Specification

Type	Resistance range (Ω)	Rated maximum current	Operating temperature	Rated ambient temperature	Packaging quantity
YJP1608	0.2±0.1mΩ Maximum resistance is less than 0.3mΩ under the operating temperature range	10A	−40 ~+125℃	+70℃	5,000pcs
YJP3216	0.2±0.1mΩ Maximum resistance is less than 0.3mΩ under the operating temperature range	20A	−40 ~+125℃	+70℃	5,000pcs

◆Dimensions



Type	Size (inch)	L	W	a	t
YJP1608	0603	1.60±0.20	0.80±0.20	0.30±0.10	0.30±0.10
YJP3216	1206	3.20±0.20	1.60±0.20	0.30±0.10	0.30±0.10

(unit : mm)

MEMO

MEMO

Power choke coils

Power choke coils
PCMB series

Small power choke coils
PCMB series, PS series

Power choke coils

■PCMB series

Features

- Low profile (3.0 mm max) and small size (7.3mm × 6.6mm)
- Small size allowing space saving on the board
- Low loss and high saturating current.

Applications

- PCs, servers, power sources, mobile devices, flat screen TVs etc.

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

PCMB 13 - *** M N(S,T)**

- PCMB — Series code
- 13** — Size : (063T=6.6×7.3×3.0mm, 104T=10×11.5×4.0mm, 133E=12.6×13.8×3.5mm, 135T=12.6×13.8×5.0mm)
- *** — Inductance value (R56=0.56μH, R68=0.68μH)
- M — Inductance tolerance : M=±20%
- N(S,T) — Material : refer to the table for electrical characteristics

Rated current : the current that increases the temperature by 40°C
Saturating current : The current that reduces inductance by 30% (PCMB/PS/PST/PL).
*Contact us for details.

◆Dimensions, Electrical characteristics



◆Equivalent circuits





Small power choke coils

■PCMB series, PS series

Features

- Low DCR and large current for small sizes
- High efficiency and low loss

Applications

- PCs, servers, power sources, mobile devices, flat screen TVs etc.

Lead free　Halogen free　RoHS Compliance

◆Part numbering system

PS 031* - *** M (S)

- PS: Series code
- 031*: Size : B(2.9mm×2.9mm×1.2mm), T(2.9mm×2.9mm×1.0mm)
- ***: Inductance value
- M: Resistance tolerance : M=±20%
- (S): Material : refer to the table for electrical characteristics

Rated current : the current that increases the temperature by 40°C
Saturating current : The current that reduces inductance by 20% (PCMC) or 30% (PCMB/PS/PST/PL)
*Contact us for details.

◆Dimensions, Electrical characteristics

PCMB type



PS*, PS type



MEMO

High frequency surface mount components

High Frequency Chip Attenuator
ATS series（Under development）

High Precision Chip Attenuator
PAT series

High Precision Chip Attenuator
(W type)
PAT series, W type

Thermo-variable chip attenuators
P＊V series

Power Splitter
PS series

High power thin film chip terminator
PCS series, HPT series



High Frequency Chip Attenuator

■ATS series

Lead free　Halogen free　RoHS Compliance

Features

- Attenuation range up to 30GHz
- Internal circuit specially designed for 0-10dB attenuation.
- Miniature surface mount chip attenuator (2012 size)
- Signal line sandwiched by ground – excellent heat dissipation and low noise.

Applications

- Wireless communication devices and base stations
- Wireless communication modules

◆Part numbering system

ATS 2012 - 10dB - T1

- ATS: Series code
- 2012: Size : ATS2012
- 10dB: Attenuation : 2 digit (example 00dB= 0dB, 10dB= 10.0dB)
- T1: Packing quantity : T1 (1,000pcs) , T05 (500pcs)

◆Electrical Specification

Type	ATS2012			
Attenuation	0dB	1~2dB(1dB step)	3~7dB(1dB step)	8~10dB(1dB step)
Circuit Type	Thru	Tee	Pi (π)	Dual pi (Dual π)
Equivalent circuits	①	②	③	④
Attenuation tolerance	±0.25dB(DC~10GHz)、 ±0.5dB(10~20GHz)、 ±0.75dB(20~30GHz)			
V S W R	TBD			
Impedance	50Ω			
Operating frequency	DC~30GHz			
Rated power	100mW			
Rated operating temperature	70℃			
Operating temperature	-55℃~+125℃			
Packaging quantity	500pcs/reel(T05) 1,000pcs/reel(T1)			

* : Same specification may be updated because this product is still under development. Please contact our Sales for the latest specification and the information related to this product.

◆Equivalent Circuit and pin arrangement





1 : Input pin
2 : Output pin
3 : GND

◆Dimensions



Type	Size (inch)	L	W	t	L1	a	W1	W2
ATS2012*1	0805	2.00±0.20	1.22±0.20	max 0.40	1.80	0.36	0.25	0.25

(unit : mm)

*1 : The terminal design and the dimension on the back side may be updated as we improve the product's performance.
Please contact our Sales for the latest specification and the information related to this product.

◆Derating Curve



High Precision Chip Attenuator

■PAT series

Features

- One chip attenuator covers wide frequency range.
- Wrap around terminal similar to regular chip resistors makes it easy to mount.
- Sizes from 1005 to 3042 are offered, which contribute to miniaturization of devices.

Lead free　Halogen free　RoHS Compliance

Applications

- Cell phone base stations
- Wireless communication modules
- Wide band measurement instrumentation

◆Part numbering system

PAT 1632 - C - 3dB - T1

- PAT: Series code
- 1632: Size : PAT0510S,PAT0816 PAT1220,PAT1632,PAT3042S
- C: Impedance: C=50Ω D=75Ω
- 3dB: Attenuation : 2 digit
- T1: Packing quantity: T=Tape (T10/T1/T2/T5), B=Bulk

◆Electrical Specification

Type	PAT0510S			PAT0816			PAT1220	PAT1632		PAT3042S	
Attenuation	0～3dB (1dB step)	4～7dB (1dB step)	8～10dB (1dB step)	0～3dB (1dB step)	4～7dB (1dB step)	8～10dB (1dB step)	0～10dB (1dB step)	0～10dB (1dB step)	16dB	0～10dB (1dB step)	16,20dB
Attenuation tolerance	±0.3dB	±0.5dB	±0.7dB	±0.3dB	±0.5dB	±0.7dB	±0.3dB	±0.3dB	±0.5dB	±0.3dB	±0.5dB
Impedance	50Ω(C)			50Ω(C)				50Ω(C)		50Ω(C), 75Ω(D)	
VSWR	<1.3			<1.3(～6GHz), <1.5(6～10GHz)			<1.3	<1.3		<1.2(50Ω), <1.3(75Ω)	
Operating frequency	DC～10GHz			DC～10GHz				DC～3GHz		DC～3GHz	
Rated power	32mW			64mW			100mW	125mW		125mW	
Rated operating temperature	70℃										
Operating temperature	−55℃~+125℃										
Packaging quantity	10,000pcs/reel (T10)			100pcs/Bag (B) 1,000pcs/reel (T1) 5,000pcs/reel (T5)						50pcs/Bag (B) 1,000pcs/reel (T1) 2,000pcs/reel (T2)	

◆Equivalent Circuit and pin arrangement

Equivalent circuit



Top side



◆Dimensions

PAT0510S



PAT0816



PAT1220



PAT1632



PAT3042S



Type	Size (inch)	L	W	t	a	c	b
PAT0510S	0402	1.00±0.05	0.50±0.05	0.34±0.05	0.12±0.04	0.27±0.05	0.25±0.05

(unit : mm)

Type	Size (inch)	L	W	t	a	b	W1	W2	W3	W4
PAT0816	0603	1.60±0.10	0.80±0.10	0.40±0.10	0.50±0.15	0.50±0.10	0.25±0.10	0.15±0.10	0.20±0.10	–
PAT1220	0805	2.00±0.10	1.25±0.10	0.40±0.10	0.50±0.20	0.60±0.20	0.40±0.20	0.40±0.20	0.35±0.20	< 0.25
PAT1632	1206	3.20±0.20	1.60±0.20	0.40±0.10	1.00±0.25	1.00±0.25	0.55±0.25	0.40±0.25	0.40±0.20	–

(unit : mm)

Type	Size (inch)	L	W	t	a	b	Lb
PAT3042S 50Ω(C)	1612	4.20±0.20	3.00±0.20	0.80±0.15	0.80±0.20	0.50±0.20	3.10±0.20
PAT3042S 75Ω(D)	1612	4.20±0.20	3.00±0.20	0.80±0.15	0.80±0.20	0.30±0.20	3.50±0.20

Type	W1	W2	Wa	W3	W4	Wb
PAT3042S 50Ω(C)	0.95±0.20	0.80±0.20	1.05±0.20	0.95±0.20	0.95±0.20	0.95±0.20
PAT3042S 75Ω(D)	0.55±0.20	0.60±0.20	1.55±0.20	0.55±0.20	0.60±0.20	1.55±0.20

(unit : mm)

High Precision Chip Attenuator

■PAT series

◆Recommended land patterns(soldering footprints)



Size	W1	Wb	L1	Lb
PAT0510S	0.30	0.20	0.35	0.37
PAT0816	0.40	0.30	0.60	0.50
PAT1220	0.70	0.50	0.80	0.70
PAT1632	0.80	0.65	1.20	1.00
PAT3042S (50Ω)	1.10	0.90	1.20	2.90
PAT3042S (75Ω)	1.00	1.10	1.00	3.30

(unit : mm)

◆Benefits of PAT series

Three resistive elements are integrated inside of this chip attenuator. If you use discrete resistors to construct an attenuator, 3 resistors are needed. The merits of one attenuator displacing 3 resistors are:

1) Three precision resistors are integrated as an attenuator. Therefore, precision attenuation can be easily achieved with this attenuator.
2) Because 3 elements are integrated in a small area, parasitic capacitance and inductance are minimized and desired attenuation can be easily attained.
3) One attenuator can replace 3 discrete resistors, which contributes miniaturizing the circuit and makes the circuit more reliable



◆Derating Curve



◆High frequency characteristics

PAT0816 3dB VSWR



PAT0816 3dB attenuation



PAT0816 6dB VSWR



PAT0816 6dB attenuation



PAT1220 3dB VSWR



PAT1220 3dB attenuation



PAT1220 6dB VSWR



PAT1220 6dB attenuation



High Precision Chip Attenuator

■PAT Series W type

Features

- Single attenuating element realizes excellent attenuating characteristics
- Wide frequency range makes it possible to handle circuits with different frequency with ease
- The distribution of the terminals, signal terminals in the middle and ground terminal at ends, are designed for easy integration to coaxial connectors

Lead free　Halogen free　RoHS Compliance

Applications

- Attenuator for coaxial lines/circuit
- Attenuator for measuring instrumentation

◆Part numbering system

PAT 3042 - C - 3dB - A - T1

- Series code
- Size : PAT3042,PAT4556,PAT3060H
- Impedance: C=50Ω
- Attenuation : 2 digit
- Attenuation tolerance
- Packing quantity: T=Tape (T1), B=Bulk

◆Electrical Specification

Type	PAT3042	PAT4556	PAT3060H
Attenuation	0-10(1dB step), 16,20dB	0-10(1dB step), 13,16,20dB	1,2,3,5,6,10dB
Attenuation tolerance	Refer table1		±0.5dB
Impedance	50Ω(C)	50Ω(C)	50Ω(C)
VSWR	<1.1(DC-2GHz) <1.2(2-5GHz), <1.3(5-10GHz)		<1.2
Operating frequency	DC ~ 10GHz		DC ~ 6GHz
Rated power	250mW	500mW	5W
Rated operating temperature	70℃		
Operating temperature	−55℃~+125℃		
Packaging quantity	50pcs/bag (B) 1,000pcs/reel (T1) 2,000pcs/reel (T2)	50pcs/bag (B) 1,000pcs/reel (T1)	100pcs/bag (B) 1,000pcs/reel (T1)

Attenuation tolerance				
Attenuuation	Rank	DC~ 2GHz	2 ~ 5GHz	5 ~ 10GHz
0~10dB	A	±0.1dB	±0.2dB	±0.4dB
0~10dB	B	±0.2dB	±0.3dB	±0.5dB
16,20dB (13dB)*	B	±0.2dB	±0.3dB	±0.5dB

*Only PAT4556

◆Equivalent Circuit and pin arrangement

Equivalent circuit



Top side



◆Dimensions

PAT3042



PAT4556



PAT3060H



Type	PAT3042					
Size(inch)	1612					
Symbol	0dB	1dB	2,3dB	4,5,6dB	7,8,9,10dB	16,20dB
L	4.2±0.20					
W	3.0±0.20					
t	0.8±0.15					
W1	0.40±0.15	0.30±0.15	0.40±0.15			
W2	0.66±0.10	0.66±0.10	0.90±0.10			
W3	0.77±0.10	0.85±0.10	0.65±0.10			
L1	—	1.90±0.20	1.90±0.20	1.75±0.20	1.60±0.20	1.15±0.20
L2	4.20±0.20	0.30±0.20	0.30±0.20	0.60±0.20	0.90±0.20	1.80±0.20

(unit : mm)

Type	PAT4556	
Size(inch)	2218	
Symbol	0dB	1 ~ 20dB
L	5.60±0.20	
W	4.50±0.20	
t	0.80±0.15	
W1	0.60±0.10	
W2	0.64±0.10	1.3±0.10
W3	0.60±0.10	

Type	PAT3060H
Size(inch)	2412
L	6.00±0.20
W	3.00±0.20
t	0.70±0.15
a	0.80±0.15
b	0.45±0.10
c	0.50±0.10
d	max 0.5

(unit : mm)

◆Recommended land patterns(soldering footprints)

PAT3060H



PCB material	Pattern A size
Glass epoxy t=0.6mm	1.07mm
Teflon t=0.6mm	1.52mm

・Refer to the information on the next page on how to use PAT3042/PAT 4556

High Precision Chip Attenuator

■PAT Series W type

◆High frequency characteristics (measured value)



Measured samples : 5pcs



Measured samples : 5pcs

◆Mounting example

The shape of this attenuator chip is designed to match coaxial connectors' shape so that it can be integrated easily. In this case, the center conductor should be soldered to the signal terminals (the middle terminals) and metallic shield should be soldered to the ground terminals (the end terminals.)



◆Derating Curve





Thermo-variable Chip Attenuator

■P*V Series

Features

- Simple solution for compensation for the temperature drift of GaAs amplifier
- Resistive construction allows operation in wide frequency range
- Ten different attenuation x 8 or 9 temperature characteristics: over 80 different offerings to meet any amplifier characteristics.

Lead free　Halogen free　RoHS Compliance

※Except for Chinese RoHS

Applications

- Cell phone base station
- Wireless remote controller

◆Part numbering system

PXV　1220S - 6dB　N1 - T

- Series code
- Size : PXV1220S, PBV1632S, PAV3137S
- Attenuation : 2 digit
- Thermo sesitive characteristic: N1~N9
- Packing quantity: T=Tape (T1), B=Bulk

◆Electrical Specification

Type	PXV1220S	PBV1632S	PAV3137S
Attenuation	1 ~ 10dB (1dB Step)	1 ~ 10dB, 16dB (1dB Step)	1 ~ 10dB (1dB Step)
Attenuation tolerance	±0.5dB(@25℃, no load)		
Impedance	50Ω		
VSWR	<1.3		
Termo Sensitive characterristic	N1 ~ N9 (1db ~ 3dB) N1 ~ N8 (4db ~ 10dB)	N1 ~ N9 (1db ~ 3dB) N1 ~ N8 (4db ~ 16dB)	N1 ~ N9 (1db ~ 3dB) N1 ~ N8 (4db ~ 10dB)
Operating frequency	DC ~ 3GHz		DC ~ 6GHz
Rated power	63mW	100mW	2W
Operating temperature	−40℃~+100℃		−40℃~+125℃
Packaging quantity	100pcs/bag(B)　1,000pcs/reel(T1)	20pcs/bag (B)　1,000pcs/reel (T1)	

◆Equivalent Circuit and pin arrangement

Equivalent circuit



Top side



◆Dimensions



Type	Size (inch)	L	W	t	b	W2	W3
PXV1220S	0805	2.00±0.20	1.25±0.20	1.1max	0.65±0.20	0.38±0.20	0.25±0.35
PBV1632S	1206	3.20±0.20	1.60±0.20	1.5max	1.00±0.20	–	0.40±0.35
PAV3137S	1512	3.70±0.20	3.10±0.20	1.5max	1.00±0.20	1.50±0.20	0.85±0.20

(unit : mm)

◆Recommended land patterns(soldering footprints)



Type	W1	W2	a	L1	b
PXV1220S	0.70	0.70	0.50	0.80	0.70
PBV1632S	0.80	0.80	0.70	1.20	1.00
PAV3137S	1.55	1.15	0.60	1.25	1.50

(unit : mm)

◆Derating Curve



Thermo-variable Chip Attenuator

■P*V Series

◆Attenuation amount temperature characteristic

PXV1220S-3dB attenuation characteristic



PXV1220S-3dB-N*

Temparature	N1	N2	N3	N4	N5	N6	N7	N8	N9
-40 ~ +25℃	-0.0243	-0.0146	-0.0105	-0.00693	-0.00433	-0.0035	-0.00273	-0.0018	-0.00117
+25 ~ +100℃	-0.0158	-0.0145	-0.0133	-0.0117	-0.00963	-0.00867	-0.00754	-0.00578	-0.00423
-40 ~ +100℃	-0.0197	-0.0145	-0.012	-0.00949	-0.00717	-0.00627	-0.0053	-0.00393	-0.00281
Temp. characteristic tolerance	max ±10%							max ±15%	

(unit : dB/℃)

PXV1220S-6dB attenuation characteristic



PXV1220S-6dB-N*

Temparature	N1	N2	N3	N4	N5	N6	N7	N8
-40 ~ +25℃	-0.145	-0.0725	-0.0388	-0.0213	-0.0166	-0.0125	-0.00794	-0.00504
+25 ~ +100℃	-0.037	-0.0351	-0.0323	-0.0282	-0.0261	-0.0235	-0.0191	-0.0148
-40 ~ +100℃	-0.0873	-0.0525	-0.0353	-0.025	-0.0217	-0.0184	-0.0139	-0.0102
Temp. characteristic tolerance	max ±10%							max ±15%

(unit : dB/℃)

PXV1220S-10dB attenuation characteristic



PXV1220S-10dB-N*

Temparature	N1	N2	N3	N4	N5	N6	N7	N8
-40 ~ +25℃	-0.0908	-0.0643	-0.0449	-0.0264	-0.0161	-0.0107	-0.00716	-0.00475
+25 ~ +100℃	-0.0601	-0.0568	-0.0525	-0.0447	-0.0362	-0.0292	-0.0227	-0.0169
-40 ~ +100℃	-0.0743	-0.0603	-0.049	-0.0362	-0.0269	-0.0206	-0.0155	-0.0113
Temp. characteristic tolerance	max ±10%						max ±15%	

(unit : dB/℃)

◆High frequency characteristics (measured value)









◆Example of use

- High frequency GaAs transistor amplifiers' gain decreases as temperature increases.
- Integrating this attenuator into amplifier circuit compensates the gain loss and keep the gain constant in the circuit. (figure below)
- Replaces complex feedback circuits.

Amplifier circuit with temperature compensation function





Power Splitter

■PS Series

Features

- Resistive type power splitter. Wide frequency range : DC to 20Ghz.
- Wide band provides less distortion of square pulses of digital signals
- Small and easy to mount
- Special design and thin film produce less reflection.

Lead free　Halogen free　RoHS Compliance

Applications

- Communication devices
- Wide band measuring instrumentation

◆Part numbering system

PS 1608 G T2 - R50 - T1

- Series code
- Size : PS1005,PS1608,PS2012 PS3216,PS5025
- G : General
- Number of Output terminals
- Impedance : 50Ω
- Packing quantity: T=Tape (T1/T5), B=Bulk

PS 1005 T2 - R50 - FD - T1

- Series code
- Size : PS1005
- Number of Output terminals
- Impedance : 50Ω
- No GND, Need Face down mounting
- Packing quantity: T=Tape (T1/T5), B=Bulk

◆Electrical Specification

Type		PS1005 ※1	PS1608G	PS2012G	PS3216G	PS5025G
Operating frequency		DC - 20GHz	DC - 20GHz	DC - 17.5GHz	DC - 15GHz	DC - 10GHz
Rated power		100mW	100mW	125mW	250mW	500mW
Insersion Loss	6dB±0.5dB	< 10GHz				< 7.5GHz
	6dB±1.0dB	< 20GHz		<17.5GHz	<15GHz	<10GHz
Distribution Deviation		< 0.3dB (Max freuency)				
VSWR	≦1.3	< 10GHz				< 7.5GHz
	≦1.5	< 20GHz		<17.5GHz	<15GHz	<10GHz
Operating temperature		-40℃ ~ +125℃				
Packaging quantity		50pcs/bag(B) 1,000pcs/reel(T1) 5,000pcs/reel(T5)				

※1　The PS1005 series has no ground plane.

◆Equivalent Circuit and pin arrangement

Equivalent circuit



Top side



◆Dimensions



Type	Size (inch)	W	L	t	a	b	e	g
PS1005	0402	1.00±0.10	0.50±0.10	0.30±0.10	0.40±0.10	0.35±0.10	—	0.20±0.10
PS1608G	0603	1.60±0.10	0.80±0.10	0.40±0.10	0.45±0.10	0.35±0.10	0.40±0.10	0.25±0.10
PS2012G	0805	2.00±0.10	1.25±0.10	0.40±0.10	0.45±0.15	0.35±0.15	0.35±0.10	0.25±0.10
PS3216G	1206	3.20±0.10	1.60±0.10	0.40±0.10	0.35±0.10	0.40±0.15	1.075±0.10	0.20±0.10
PS5025G	2010	5.00±0.20	2.50±0.20	0.80±0.20	0.50±0.20	0.75±0.20	1.65±0.20	0.30±0.15

(unit : mm)

◆Recommended land patterns (soldering footprints)



* Face down mounting









◆Derating Curve





High Power Thin Film Chip Terminator

■PCS Series、HPT Series

Lead free　Halogen free　RoHS Compliance

Features

- Small high power chip terminator with aluminum nitride and aluminum oxide substrate
- Efficient heat dissipation provides high power, anti-surge, overload protection.
- Wrap around terminals provide easy and reliable soldering.
- Thin film does not have any innate stress. Therefore, repeated power cycling does not fatigue the element and cause no change in impedance.

Applications

- Wireless base station, wireless communication devices, and high frequency power source

◆Part numbering system

HPT 3216 - 50 - T1

- HPT: Series code(PCS, HPT)
- 3216: Size : 1005,1608,2012,3216,5025 6432, *6464, *9464H　*HPT series only
- 50: Impedance
- T1: Packing quantity: T=Tape (T1/T5), B=Bulk

◆Electrical Specification

PCS series (Alumina substrate)

Type		PCS1005	PCS1608	PCS2012	PCS3216	PCS5025	PCS6432
Rated Power		200mW	500mW	1W	2W	5W	10W
VSWR	DC ～ 3GHz	1.2	1.2	1.2	1.2	1.3	1.2
	3.1～5GHz	1.2	1.2	1.3	1.3	1.4	1.5
	5.1～7.5GHz	1.3	1.3	1.3	1.4	1.5	—
	7.6～10GHz	1.3	1.3	1.4	1.5	—	—
	10.1～12.5GHz	1.4	1.4	1.5	—	—	—
	12.6～15GHz	1.5	1.5	—	—	—	—
Operating temperature		-55℃～+125℃					
Rated operating temperature		+70℃					
Packaging quantity		100/bag (B) 1000pcs/reel (T1) 5000pcs/reel (T5)					

HPT series (ALN substrate)

Type		HPT1608	HPT2012	HPT3216	HPT5025	HPT6432	HPT6464	HPT9464H
Rated Power		2.5W	5W	10W	20W	30W	60W	100W
VSWR	DC ～ 3GHz	1.2	1.2	1.2	1.3	1.3	1.3	1.3
	3.1～5GHz	1.2	1.3	1.3	1.5	1.5	—	—
	5.1～7.5GHz	1.3	1.3	1.4	—	—	—	—
	7.6～10GHz	1.3	1.4	1.5	—	—	—	—
	10.1～12.5GHz	1.4	1.5	—	—	—	—	—
	12.6～15GHz	1.5	—	—	—	—	—	—
Operating temperature		-40℃～+155℃						
Rated operating temperature		+100℃ at Terminal						
Packaging quantity		100/bag (B) 1000pcs/reel (T1) 5000pcs/reel (T5)						100/bag(B) 1000pcs/reel (T1)

◆Dimension, Equivalent Circuit and pin arrangement

Equivalent circuit



PCS1608



PCS2012 PCS3216 PCS5025



PCS6432



Type	Size (inch)	L	W	t	L1	L2	L3
PCS1005	0402	1.00±0.10	0.50±0.10	0.30±0.10	0.65±0.10	0.20±0.10	0.15±0.10
PCS1608	0603	1.60±0.15	0.80±0.15	0.40±0.10	1.10±0.15	0.30±0.15	0.20±0.15
PCS2012	0805	2.00±0.15	1.25±0.15	0.40±0.10	1.50±0.15	0.30±0.15	0.20±0.15
PCS3216	1206	3.20±0.20	1.60±0.20	0.40±0.10	2.70±0.20	0.30±0.15	0.20±0.15
PCS5025	2010	5.00±0.20	2.50±0.20	0.40±0.10	4.30±0.20	0.40±0.15	0.30±0.15
PCS6432	2512	6.40±0.20	3.20±0.20	0.40±0.10	5.70±0.20	0.40±0.15	0.30±0.15

HPT1608 HPT2012
HPT3216 HPT5025



HPT 6432



HPT6464 HPT9464H



Type	Size (inch)	L	W	t	L1	L2	L3	W1
HPT1608	0603	1.60±0.15	0.80±0.15	0.40±0.10	1.10±0.15	0.30±0.15	0.20±0.15	–
HPT2012	0805	2.00±0.15	1.25±0.15	0.40±0.10	1.50±0.15	0.30±0.15	0.20±0.15	–
HPT3216	1206	3.20±0.20	1.60±0.20	0.40±0.10	2.70±0.20	0.30±0.15	0.20±0.15	–
HPT5025	2010	5.00±0.20	2.50±0.20	0.65±0.10	3.60±0.20	0.90±0.20	0.50±0.15	–
HPT6432	2512	6.40±0.20	3.20±0.20	0.65±0.10	5.50±0.20	0.70±0.15	0.20±0.15	–
HPT6464	2525	6.30±0.20	6.30±0.20	0.65±0.10	4.90±0.20	0.65±0.15	0.75±0.15	3.05±0.20
HPT9464H	3725	9.40±0.20	6.30±0.20	0.65±0.10	7.10±0.20	1.15±0.15	1.15±0.15	3.00±0.20

(unit : mm)

High Power Thin Film Chip Terminator

■PCS Series、HPT Series

◆Recommended land patterns (soldering footprints)

PCS／HPT



Type	a	b	c
PCS1005	0.70	0.20	0.70
PCS1608	1.20	0.30	1.20
PCS2012	1.20	0.45	1.60
PCS3216	2.00	0.45	2.00
PCS5025	2.90	0.55	2.90
PCS6432	3.60	0.55	3.60

(unit : mm)

Type	a	b	c
HPT1608	1.20	0.40	1.20
HPT2012	1.60	0.40	1.50
HPT3216	2.00	0.40	2.00
HPT5025	2.90	0.90	2.90
HPT6432	3.60	0.70	3.60
HPT6464	3.30	1.15	6.80
HPT9464H	3.30	1.15	6.80

(unit : mm)

◆Mounting example

Pay special care to heat dissipation when this product is used at maximum rated power.

Mounting example of these series



Above diagram shows a mounting example with thermal bias dissipating heat to the ground. Depending on the application, a heat sink might be needed closely contacting to the bottom of the product.

◆Derating Curve

○ PCS Series



○ HPT Series



◆High frequency characteristics

PCS1608 VSWR



PCS3216 VSWR



PCS6432 VSWR



MEMO

Sample kits

Sample kits

<BOX>

<FILE>

Sample kits

Kits are available for metal thin film chip resistors and low resistance chip resistors.
They are perfect for development, prototype making, testing and experiments.

◆Part numbering system

RG1005PD - KIT - BOX(FILE)

- RG1005PD: Product series name
- KIT: Sample kits
- BOX(FILE): Packaging quantity:BOX(BOXType) FILE : (Filing book type)

◆Electrical Specification

Surface mount thin film resistors / Metal thin film chip resistors

Electrical characteristics	Rated power(W)						Resistance tolerance(%)			Container type	
	1/4	1/6	1/8	1/10	1/16	1/32	±0.05	±0.1	±0.5	BOX	FILE
RR0816PD-KIT					●				●	●	●
RR1220PD-KIT				●					●	●	●
RG1005PD-KIT			●		●	●			●	●	●
RG1608PD-KIT		●		●	●				●	●	●
RG2012PD-KIT	●		●	●					●	●	●
RG1005PB-KIT			●		●	●		●		●	●
RG1608PB-KIT		●		●	●			●		●	●
RG2012PB-KIT	●		●	●				●		●	●
RG1005NW-KIT			●		●	●	●			●	●
RG1608NW-KIT		●		●	●		●			●	●
RG2012NW-KIT	●		●	●			●			●	●

Current sensing surface mount resistors / Low resistance chip resistors

Electrical characteristics	Rated power(W)										Resistance tolerance(%)		Container type	
	6	5	4	3	2	1.5	1	3/4	1/2	1/3	±1	±2	BOX	FILE
KRL1220-KIT									●		●	●		●
KRL1632-KIT								●			●	●		●
KRL3264-KIT					●						●	●		●
KRL2012-KIT							●				●	●		●
KRL3216-KIT						●					●	●		●
KRL6432-KIT				●							●	●		●
KRL7638-KIT			●								●	●		●
KRL9045-KIT		●									●	●		●
KRL11050-KIT	●										●	●		●
RL1220-KIT										●	●			●
RL3720W-KIT							●				●			●

Sample kits

MEMO

MEMO

Standard Specification for surface mount chip resistors

This standard specification describes shared specifications among surface mount chip resistors regarding placement and packaging.
Custom products and products in development may not be included in these specifications.
Contact our sales office for these products.

These specifications may not be applicable to power choke products and high frequency components. Contact our sales office for these products.

1. Recommended land patterns (soldering footprints)

①For thin film chip resistor

②For current sensing chip resistor

2. Recommended reflow soldering profile

3. Dimensions of the packaging tape

①For thin film chip resistor

②For current sensing chip resistor

4. Dimensions of the packaging reel

Recommended land patterns (soldering footprints)

① For thin film chip resistor

【Applicable series】

· URG series · RG series · RGT series · NRG series · MRG series · RGA series[*1]
· RS series · RR series · RT series

Recommended land dimensions (mm)			
Sizes	a	b	c
0603	0.28	0.76	0.34
1005	0.5	1.6	0.6
1608	1.0	3.0	1.2
2012	1.2	4.0	1.65
3216	2.2	5.0	2.0
5025	3.8	6.8	2.9
6432	4.8	8.2	3.6

*1 RGA is compatible with conductive epoxies.
Please contact our sales office for details for conductive epoxy usage.



【Applicable series】

· PRG series

Recommended land dimensions (mm)				
Sizes	a	b	c	d [(*1)] (reference)
2010[*2]				
3216	0.8	1.1	3.7	≧27
5020	1.3	1.6	5.7	≧27
6432	2	2.1	6.9	≧27

*1 Please design the land pattern considering heat dissipation to the board so that the terminal temperature will not exceed 155°C.
*2 In development



【Applicable series】

· HRG series

Recommended land dimensions (mm)				
Sizes	a	b	c	d [(*1)] (reference)
3216	0.55	1.9	1.8	≧27

*1 Please design the land pattern considering heat dissipation to the board so that the terminal temperature will not exceed 155°C.



【Applicable series】

・RM series[*1]　・RMA series[*2]

◯ 4 terminal type

Recommended land dimensions (mm)						
Sizes	a	b	c	d	e	f
RM/RMA2012	0.6～0.7	1.6～1.8	0.4～0.6	1.8～2.0	0.7～0.9	1.3～1.5
RM/RMA3216	0.6～0.8	2.4～2.7	0.6～0.8	2.6～3.2	1.4～1.6	2.2～2.4
RM/RMA3225	1.5～1.7	3.3～3.6	0.6～0.8	2.6～3.2	1.4～1.6	2.2～2.4



◯ 6 terminal type

Recommended land dimensions (mm)						
Sizes	a	b	c	d	e	f
RM3216	0.5～0.7	2.4～2.7	0.6～0.8	2.5～2.7	0.2～0.3	0.9～1.0
RM3225	1.3～1.5	3.3～3.6	0.6～0.8	2.5～2.7	0.2～0.3	0.9～1.0



◯ 8 terminal type

Recommended land dimensions (mm)						
Sizes	a	b	c	d	e	f
RM3216	0.7～0.8	2.2～2.3	0.4～0.45	2.9～3.0	0.3～0.35	0.8～0.85
RM3225	1.4～1.5	3.4～3.5	0.4～0.45	2.9～3.0	0.3～0.35	0.8～0.85
RM6432	1.9～2.0	4.0～4.1	0.85～0.9	5.7～5.8	0.7～0.75	1.6～1.65



*1 Custom RM requires custom land patterns. Please contact us.
*2 RMA is compatible with conductive epoxies . Please contact our sales office for details for conductive epoxy usage.

Recommended land patterns (soldering footprints)

② For current sensing chip resistor

【Applicable series】

・KRL series (long side terminal)

Recommended land dimensions (mm)					
Types	Resistance range	Copper foil thickness (um)	a	b	c
KRL1608D	10mΩ~		0.25	1.60	1.70
KRL2012D/E	1mΩ*1	100	0.25	2.00	2.20
	2mΩ~	35	0.60		
KRL3216D/E	1mΩ*1	100	0.40	2.40	3.40
	2mΩ~	35	0.60		
KRL5025D/E	1mΩ*1	35	0.70	4.00	5.20
	2mΩ~	100	1.20		
KRL6432D/E	1mΩ*1		0.70	4.20	6.60
	2mΩ~		2.20		
KRL7638D/E	1mΩ*1		1.10	4.60	7.80
	2mΩ~		2.60		
KRL9045D/E	1mΩ*1		1.30	5.10	9.20
	2mΩ~		3.10		
KRL11050D/E	1mΩ*1		1.80	5.60	11.20
	2mΩ~		3.60		
KRL15075D/E	1mΩ*1		2.00	8.40	15.20
	2mΩ~		5.00		

*1 Refer to the diagram right for the Land pattern of 1mΩ



*1 KRL2012D/E, KRL3216D/E, KRL5025D/E, KRL6432D/E, KRL7638D/E, KRL9045D/E, KRL11050D/E, KRL15075D/E : 1mΩ



【Applicable series】

・KRL series (Short side terminal)

Recommended land dimensions (mm)					
Types	Resistance range	Copper foil thickness (um)	a	b	c
KRL0816D/E	10~18mΩ*1	35	0.10	2.20	1.00
	20~39mΩ*1		0.50		
	43mΩ~	100	0.90		
KRL1220D/E	5mΩ~	100	1.20	2.70	1.50
KRL1632D/E	5 ~ 8mΩ		1.00	4.00	1.90
	9mΩ~		2.00		
KRL2550D/E	5 ~ 8mΩ		2.20	6.00	2.80
	9mΩ~		3.80		
KRL3264D/E	5 ~ 8mΩ		2.50	7.40	3.50
	9mΩ~		4.40		
KRL50110D/E	5 ~ 8mΩ		2.80	14.00	5.75
	9mΩ~		5.50		

*1 Refer to the diagram right for the land pattern of KRL0816D/E



*1 KRL0816D/E : 10 ~ 18mΩ, 20 ~ 39mΩ



【Applicable series】

· KRL series (4terminal type)

Recommended land dimensions (mm)					
Types	a	b	c	d	e
KRL3216T4	0.40	2.70	0.35	0.30	2.70
KRL6432T4	2.00	4.40	0.70	0.50	5.40
KRL7638T4	2.00	4.40	1.00	0.60	6.30
KRL9045T4	2.60	5.00	1.20	0.70	7.50
KRL11050T4	3.20	5.60	1.60	1.10	8.70



【Applicable series】

· RL Series (Short side terminal)

Recommended land dimensions (mm)			
Sizes	a	b	c
0510	0.5	1.9	0.7
0816	0.7	3.0	1.6
1220	1.0	4.0	2.4



【Applicable series】

· RL Series (Short side terminal)

Recommended land dimensions (mm)				
Sizes	a	b	c	d
RL3720W	1.2	7.9	7.9	27.0
RL7520W	1.2	15.8	15.8	27.0



Recommended reflow soldering profile



Product surface temperature

pre-heating	130 ~ 180℃ 60 ~ 90sec.
Reflow	above 220℃ 30 ~ 90sec.
Peak temperature	240 ~ 250℃ Maximum 10 seconds · Applicable solder composition : Sn−Ag−Cu solder paste · Cycles : twice (cooling between 1st and 2nd cycles)

Dimensions of the packaging tape

① For thin film chip resistor

Tape dimensions (paper 2 mm pitch)

Types	a	b	T
RR0306/ RT0603	0.38±0.03	0.68±0.03	0.31+0.02
RR/RT0510	0.63±0.05	1.13±0.05	0.43±0.05
RG/RGT/RS/ RGA1005	0.63±0.05	1.13±0.05	0.43±0.05
RL0510	0.63±0.05	1.13±0.05	0.43±0.05



Tape dimensions (paper 4 mm pitch)

Types	a	b	T
RR/RT/0816	1.1±0.1	1.9±0.1	0.6±0.05
URG/RG/RGT NRG/RGA1608	1.1±0.1	1.9±0.1	0.6±0.05
RL0816	1.1±0.1	1.9±0.1	0.6±0.05
RR/RT1220	1.65±0.2	2.4±0.2	0.75±0.05
URG/RG/RGT/MRG/ NRG/RGA2012	1.65±0.2	2.4±0.2	0.75±0.05
RL1220	1.65±0.2	2.4±0.2	0.75±0.05



Tape dimension (embossed tape 4mm pitch)



Types	A	B	W	F	E	P_0	P_1	P_2	φD_0	φD_1	T	t
RM2012	1.6±0.2	2.4±0.2	8.0±0.3	3.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.05±0.05	1.5max	0.3max
URG/RG/ NRG/PRG/HRG/ MRG3216	2.0±0.2	3.6±0.2	8.0±0.3	3.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.05±0.05	1.5max	0.3max
RM/RMA3216	2.0±0.2	3.6±0.2	8.0±0.3	3.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.05±0.05	1.5max	0.3max
RM/RMA 3225	2.8±0.1	3.5±0.1	8.0±0.3	3.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.1±0.1	1.0±0.1	0.3max
PRG 5020	2.8±0.1	5.3±0.1	12.0±0.2	5.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.1±0.1	1.0±0.1	0.3max
URG 5025	2.8±0.1	5.3±0.1	12.0±0.2	5.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.1±0.1	1.0±0.1	0.3max
PRG6432 /RM6432	3.5±0.2	6.9±0.2	12.0±0.2	5.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.50+0.1/-0	0.75±0.1	0.3max

Dimensions of the packaging tape

② For current sensing chip resistor

Tape dimensions (embossed tape)

○ 4 mm pitch



○ 8 mm pitch



Types	A	B	W	F	E	P_0	P_1	P_2	φD_0	φD_1	T	t
KRL0816 /1608	0.95±0.05	1.85±0.05	8.0±0.1	3.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.5+0.1/-0	0.6±0.05	0.55±0.05	0.2±0.05
KRL1220 /2012	1.45±0.05	2.3±0.1	8.0±0.2/-0	3.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.5+0.1/-0	-	0.65±0.1	0.2±0.05
KRL1632 /3216	1.9±0.1	3.5±0.1	8.0±0.2	3.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.5+0.1/-0	1.0+0.2/-0	0.75±0.1	0.2±0.05
KRL2550 /5025	2.9±0.2	5.3±0.2	12.0±0.3	5.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.5+0.1/-0	1.5+0.2/-0	1.5max	0.3max
KRL3264/6432 KRL6432T4	3.43±0.2	6.63±0.2	12.0±0.3	5.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.5+0.1/-0	1.5+0.2/-0	0.76±0.1	0.2±0.05
KRL7638 KRL7638T4	4.15±0.1	7.95±0.1	16.0±0.3	7.5±0.1	1.75±0.1	4.0±0.1	8.0±0.1	2.0±0.1	1.5±0.1	1.5±0.1	1.2±0.15	0.3±0.05
KRL9045 KRL9045T4	4.85±0.1	9.35±0.1	16.0±0.3	7.5±0.1	1.75±0.1	4.0±0.1	8.0±0.1	2.0±0.1	1.5±0.1	1.5±0.1	1.2±0.15	0.3±0.05
KRL50110 /11050 KRL11050T4	5.4±0.1	11.5±0.1	24.0±0.3	11.5±0.1	1.75±0.1	4.0±0.1	8.0±0.1	2.0±0.1	1.5±0.1	1.5±0.1	1.2±0.15	0.3±0.05

Types	A	B	W	F	E	P_0	P_1	P_2	φD_0	φD_1	T	t
SHR6432	3.5±0.2	6.9±0.2	12.0±0.2	5.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.50+0.1/-0	1.50+0.1/-0	0.75±0.1	0.3max

Types	A	B	W	F	E	P_0	P_1	P_2	φD_0	φD_1	T	t
RL3720W	2.6±0.2	4.45±0.2	12.0±0.2	5.5±0.05	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.05	1.55±0.05	–	0.7±0.1	0.3±0.05
RL7520W	2.6±0.2	8.2±0.2	16.0±0.3	7.5±0.1	1.75±0.1	4.0±0.1	4.0±0.1	2.0±0.1	1.55±0.05	–	0.7±0.1	0.3±0.05

Dimensions of the packaging reel

【Applicable series】

・URG series ・RG series ・RGT series ・NRG series ・RS series ・PRG series ・HRG series
・MRG series ・RGA series ・RR series ・RT series ・RM series ・RMA series



【Applicable series】

・KRL series（long side terminal） ・KRL series（short side terminal） ・KRL series（4 terminals）



Sizes	pieces / reel	φA	φH	E	φN	W1	W2
0816/1608 1220/2012 1632/3216	1,000/5,000	180+0/-3.0	13±0.2	2±0.5	60+1.0/-0.0	9±0.3	13±1.4
2550/5025 3264/6432	1,000 5,000	180+0/-3.0 255±1.0	13±0.2 13±0.2	2±0.5 2±0.5	60+1.0/-0.0 80±0.5	13±0.3 13.5±1.0	17±1.4 ≦18.4
7638 9045	1,000 5,000	180+0/-3.0 330±2.0	13±0.2 13±0.2	2±0.5 2±0.5	60+1.0/-0.0 80±1.0	17.0±0.3 17.4±1.0	19.4±1.0 21.4±1.0
50110/11050	1,000	180+0/-3.0	13±0.2	2±0.5	80±1.0	25.4±1.0	29.4±1.0

MEMO

Standard Specification for High frequency surface mount components

This standard specification describes shared specifications among high frequency surface mout components regarding mounting and packaging. However, since the land pattern differs depending on each series, please refer to the contents of each series description.

Custom products and products in development may not be included in these specifications.
Please contact our sales office for these products

1. Recommended reflow soldering profile

2. Dimensions of the packaging tape

3. Dimensions of the packaging reel

Recommended reflow soldering profile



Product surface temperature

pre-heating	130 ~ 180℃ 60 ~ 90sec.
Reflow	above 220℃ 30 ~ 90sec.
Peak temperature	240 ~ 250℃ Maximum 10 seconds · Applicable solder composition : Sn - Ag - Cu solder paste · Cycles : twice (cooling between 1st and 2nd cycles)

* Regarding the reflow soldering profiles of PXV series and PBV series, Please contact our sales office.

Dimension of the pakaging tape

For high frequency components

Tape dimensions

Fig.1 Paper 2mm pitch



Fig. 2 Embossed tape 4mm



Fig.3 Embossed tape 8mm pitch



Type	Refer fig.	A	B	W	F	E	P0	P1	P2	D0	D1	T	t
PAT Series													
PAT0510S	1	0.65±0.03	1.15±0.03	8.00±0.30	3.50±0.05	1.75±0.10	4.00±0.10	2.00±0.05	–	1.5±0.1/-0	–	–	0.50±0.10
PAT0816	2	0.95±0.05	1.85±0.05					4.00±0.10	2.00±0.05		0.60±0.05	0.55±0.05	0.20±0.05
PAT1220	2	1.45±0.10	2.30±0.10								–	0.65±0.01	0.20±0.05
PAT1632	2	2.00±0.20	3.60±0.20								–	2.5max	0.3max
PAT3042S	3	3.5±0.20	4.60±0.20	12.00±0.30	5.50±0.05			8.00±0.10			–	1.6max	0.4max
PAT Series, W type													
PAT3042	3	3.50±0.20	4.60±0.20	12.00±0.30	5.50±0.05	1.75±0.10	4.00±0.10	8.00±0.10	2.00±0.05	1.5+0.1/-0	–	1.6max	0.3max
PAT4556	3	4.90±0.10	6.10±0.10								1.05±0.05	1.60±0.10	0.30±0.05
PAT3080H	2	3.43±0.20	6.63±0.20					4.00±0.10			1.5+0.2/-0	1.5max	0.20±0.05
P*V Series													
PXV1220S	2	1.45±0.10	2.30±0.10	8.00±0.30	3.50±0.05	1.75±0.10	4.00±0.10	4.00±0.10	2.00±0.05	1.5+0.1/-0	1.0+0.2/-0	1.30±0.20	0.25±0.05
PBV1632S	2	2.00±0.20	3.60±0.20								–	–	0.3max
PAV3137S	3	3.30±0.10	4.30±0.10	12.00±0.30	5.50±0.05			8.00±0.05			1.5±0.1/-0	1.55±0.10	0.20±0.05
PS Series													
PS1005	1	0.65±0.03	1.15±0.03	8.00±0.30	3.50±0.05	1.75±0.10	4.00±0.10	2.00±0.05	–	1.5+0.1/-0	–	–	0.50±0.10
PS1608	2	0.95±0.05	1.85±0.05					4.00±0.10	2.00±0.05		0.06±0.10	0.55±0.05	0.20±0.05
PS2012	2	1.60±0.20	2.40±0.20								–	1.5max	0.3max
PS3216	2	1.90±0.10	3.50±0.10								1.05±0.05	1.00±0.20	0.20±0.05
PS5025	2	2.90±0.10	5.30±0.10	12.00±0.30	5.50±0.05						1.5+0.2/-0	1.00±0.05	0.20±0.05
PCS Series													
PCS1005	1	0.66±0.03	1.18±0.03	8.00±0.30	3.50±0.05	1.75±0.10	4.00±0.10	2.00±0.05	–	1.5+0.1/-0	–	–	0.50±0.10
PCS1608	2	0.95±0.05	1.85±0.05					4.00±0.10	2.00±0.05		0.60±0.10	0.55±0.05	0.20±0.05
PCS2012	2	1.45±0.10	2.30±0.10								–	0.65±0.10	0.20±0.05
PCS3216	2	1.90±0.10	3.50±0.10								1.0+0.2/-0	0.80±0.10	0.20±0.05
PCS5025	2	2.90±0.10	5.35±0.10	12.00±0.30	5.50±0.05						1.0+0.2/-0	0.75±0.10	0.20±0.05
PCS6432	2	3.43±0.20	6.63±.0.20								1.0+0.2/-0	1.5max	0.20±0.05
HPT Series													
HPT1608	2	0.95±0.05	1.85±0.05	8.00±0.30	3.50±0.05	1.75±0.10	4.00±0.10	4.00±0.10	2.00±0.05	1.5+0.1/-0	0.60±0.10	0.55±0.05	0.20±0.05
HPT2012	2	1.45±0.10	2.30±0.01								–	0.65±0.10	0.20±0.05
HPT3216	2	1.90±0.10	3.50±0.01								1.0+0.2/-0	0.75±0.10	0.20±0.05
HPT5025	2	2.90±0.2	5.30±0.20	12.00±0.30	5.50±0.05						1.5+0.2/-0	1.5max	0.3max
HPT6432	2	3.43±0.20	6.63±0.20								1.5+0.2/-0	0.76±0.10	0.20±0.05
HPT6464	3	6.60±0.10	6.70±0.10					8.00±0.10	2.0±0.10		1.5+0.2/-0	1.55±0.10	0.30±0.05
HPT9464	3	6.73±0.10	9.80±0.10	16.0+0.3/-0.1	7.50±0.10						1.5+0.2/-0	0.79±0.10	0.279±0.02

* ATS series is under development and is not described.
Regarding tape specifications, please contact our sales office.

(unit : mm)

Dimension of the pakaging reel

For high frequency components

Reel dimensions



Reel size	ϕA	ϕH	E	ϕN	W1	W2
Size 1	180+0/-3	13.0±0.2	2.0±0.5	60+1/-0	9±0.3	13.0±1.4
Size 2	180+0/-3	13.0±0.2	2.0±0.5	60+1/-0	13.0±0.3	17.0±1.4
Size 3	255±1.0	13.0±0.3	2.0±0.2	80±0.5	13.5±1.0	max 18.4
Size 4	330±2.0	13.0±0.2	2.0±0.5	100±0.5	25.4±1.0	29.4±1.0

(unit : mm)

Type	Packaging Q'ty/reel	Reel size
PAT Series		
PAT0510S	10,000	Size 1
PAT0816	1,000/5,000	Size 1
PAT1220	1,000/5,000	Size 1
PAT1632	1,000/5,000	Size 1
PAT3042S	1,000/2,000	Size 2
PAT Series, W type		
PAT3042	1,000	Size 2
PAT4556	1,000	Size 2
PAT3080H	1,000	Size 2
P*V Series		
PXV1220S	1,000	Size 1
PBV1632S	1,000	Size 1
PAV3137S	1,000	Size 1
PS Series		
PS1005	1,000/5,000	Size 1
PS1608	1,000/5,000	Size 1
PS2012	1,000/5,000	Size 1
PS3216	1,000/5,000	Size 1
PS5025	1,000/5,000	Size 3

Type	Packaging Q'ty/reel	Reel size
PCS Series		
HPT1608	1,000/5,000	Size 1
HPT2012	1,000/5,000	Size 1
HPT3216	1,000/5,000	Size 1
HPT5025	1,000/5,000	Size 1
HPT6432	1,000/5,000	Size 1
HPT6464	1,000	Size 1
HPT9464	5,000	Size 3
HPT Series		
HPT1608	1,000/5,000	Size 1
HPT2012	1,000/5,000	Size 1
HPT3216	1,000/5,000	Size 1
HPT5025	1,000	Size 2
HPT6432	5,000	Size 3
HPT6464		
HPT9464	1,000	Size 4

MEMO

Sales offices - ASIA -

ASIA

ASIA

Chip One Stop, Inc.
Sales office : Yokohama city, Japan
URL http://www.chip1stop.com/web/USA/en/

Kuroda Electric Co., Ltd.
Sales office Singapore, Indonesia, Malaysia, Thailand, Vietnam, Philipines, Taiwan, India, Korea
URL https://www.kuroda-electric.co.jp/english/profile/oversea

TAIWAN

CYNTEC CO., LTD.
URL http://www.cyntec.com
Mail service@cyntec.com

Multicom Technology LTD.
URL http://www.multicom.com.tw/index.html
Mail sales@multicom.com.tw

Walter Electronic CO. LTD.
URL http://www.walterfuse.com
Mail walter@walterfuse.com

SINGAPORE

SUSUMU SINGAPORE PTE.LTD.
629 Aljunied Road #03-20, Cititech Industrial Building, Singapore, 389838
TEL +65-6741-4070 FAX +65-6741-2971
URL http://www.susumu.sg/
Mail ssm-sg@susumu.co.jp

Exer Technologies Pte Ltd
URL http://www.exercorp.com/index.html
Mail billy@exercorp.com

KANADEN CORPORATION SINGAPORE PTE. LTD.
URL https://www.kanaden.co.jp/en/corporate/network/

Megagoal PTE LTD
URL http://www.megagoal.com
Mail enquiry@megagoal.com

Future Electronics Inc
URL http://www.futureelectronics.com

KOREA

Alliedchips Korea Co., Ltd.
URL http://www.alliedchips.co.kr
Mail master@alliedchips.co.kr

Gillanix Corporation
URL http://www.gillanix.com/
Mail jonh.jeong@gillanix.com

SAMYOUNG S&C Co., Ltd.
URL http://www.samyoungsnc.com/
Mail sales@samyoungsnc.com

SHINWOO COMMERCE CO.,LTD.
Mail ejkim@kst.ne.kr

INDIA

Megagoal PTE LTD
URL http://www.megagoal.com/
Mail enquiry@megagoal.com

CHINA

SUSUMU INTERNATIONAL TRADING (SHANGHAI) CO., LTD.
Room422, 3U Building, 8 Huajing Road, Pilot Free Trade Zone, Shanghai City P.R.C, 200131
TEL +86-21-5046-4992 FAX +86-21-5046-4993
URL http://www.susumu.sh.cn/
Mail susumu@susumu.sh.cn

Ameya Holding Limited
Office Shanghai、Shenzhen
URL http://www.ameya360.com
Mail service@ameya360.com

Elematec Trading Co.,Ltd.
Office Shanghai、Nanjing、Wuxi、Suzhou、Hangzhou、Shenzhen、Changsha、Xiamen、Canton、Zhuhai、Hong Kong
URL http://www.elematec.com/en/info/map/overseas/

KANADEN CORPORATION LTD.
Office Shanghai
URL https://www.kanaden.co.jp/en/corporate/network/

Suzhou Industrial Park JingDian Electronics Co.,Ltd
URL http://www.simon-jd.com
Mail service@simon-jd.com

Suzhou Walter Electronic Co.,Ltd
URL http://www.walterfuse.com
Mail bs.ang@walterfuse.cn

Willas-Array Electronics Limited
URL http://www.willas-array.com
Mail arc-sales@willas-array.com
(Shanghai - Northern China Sales Offices)
Mail sac-sales@willas-array.com
(Shenzhen- Southern China Sales Offices)

Xiamen Holder Electronics Co., Ltd.
Sino Faith Technology Development Ltd.
URL http://www.xmholder.com/index.aspx
Mail xmholder@xmholder.com

SHANGHAI KURODA MANAGEMENT CO., LTD
Office Shanghai、Tianjin、Nanjing、Shenzhen
URL https://www.kuroda-electric.co.jp/english/profile/oversea

HONGKONG

KANADEN CORPORATION (H.K.) LTD.
URL https://www.kanaden.co.jp/en/corporate/network/

Willas-Array Electronics(Hong Kong)Ltd.
URL http://www.willas-array.com
Mail wae@willas-array.com(Hong Kong Headquarter)

Z. KURODA (HONGKONG) CO., LTD.
URL https://www.kuroda-electric.co.jp/english/profile/oversea

Sales offices - NORTH AMERICA -

North America

Digi-Key Corporation
URL http://www.digikey.com

Future Electronics Inc.
URL http://www.futureelectronics.com

Advanced MP Technology, Inc.
URL http://www.advancedmp.com

Newark element14
URL http://www.newark.com

Mouser Electronics, Inc.
URL http://www.mouser.com

Arrow Electronics
URL http://www.arrow.com
Mail websupport@arrow.com

KURODA ELECTRIC U.S.A. INC.
Sales office : Michigan, Santa Clara, Tennessee,
San Diego, Mexico
URL https://www.kuroda-electric.co.jp/english/profile/oversea



SUSUMU INTERNATIONAL(USA) INC. East Coast Office(HQ)
460 Bergen Blvd.,Suite 226, Palisades Park, NJ 07650 USA
TEL +1-201-461-4861 FAX +1-201-461-4862
URL http://www.susumu-usa.com/
Mail info@susumu-usa.com

SUSUMU INTERNATIONAL(USA) INC. West Coast Office
4100 Moorpark Ave., Suite 206 , San Jose, CA 95117 USA
TEL +1-408-260-1112 FAX +1-408-260-1113
Mail tech@susumu-usa.com

SUSUMU INTERNATIONAL(USA) INC. North Branch Office
1546 Tower Blvd., North Mankato, MN 56003 USA
TEL +1-507-369-3498
Mail tech@susumu-usa.com

EUROPE・MIDDLE EAST

EUROPE&MIDDLE EAST

GERMANY

SUSUMU DEUTSCHLAND GmbH
Frankfurter Strasse 63-69, 7th Floor, D-65760,
Eschborn / Germany
TEL +49-6196-969-8407　FAX +49-6196-969-8879
URL http://www.susumu.de/
Mail info@susumu.co.jp

Endrich Bauelemente Vertriebs GmbH
URL http://www.endrich.com/
Mail endrich@endrich.com

MEGATRON Elektronik GmbH & Co. KG
URL http://www.megatron.de
Mail : sales@megatron.de

Gudeco Elektronik Handelsgesellschaft mbH
URL http://www.gudeco.de/
Mail info@gudeco.de

Schukat electronic Vertriebs GmbH
URL http://www.schukat.com
Mail info@schukat.com

Rutronik Elektronische Bauelemente GmbH
URL http://www.rutronik.com
Mail rutronik@rutronik.com

WDI AG
URL http://www.wdi.ag
Mail info@wdi.ag

BELGIUM

Batenburg Mechatronica
URL https://batenburg-mechatronica.nl/
Mail sales-me@batenburgbelgie.be



FRANCE

Manudax France
URL http://www.manudax.fr/
Mail manudax@manudax.fr

NETHERLANDS

Batenburg Mechatronica
URL https://batenburg-mechatronica.nl/
Mail info.mechatronica@batenburg.nl

ITALY

Avnet Abacus
URL http://www.avnet-abacus.eu/
Mail milano@avnet-abacus.eu

CZECH REPUBLIC

Has Lanskroun GmbH
URL http://www.hasdc.cz/
Mail sekretariat@hasdc.cz

KURODA ELECTRIC CZECH s.r.o.
URL https://www.kuroda-electric.co.jp/english/profile/oversea

DENMARK

Rhopoint Nordic Aps.
URL http://www.rhopointnordic.com/
Mail sales@rhopointnordic.com

EUROPE・MIDDLE EAST

EUROPE&MIDDLE EAST

AUSTRIA
Endrich Ges.m.b.H
URL http://www.endrich.com/
Mail austria@endrich.com

HUNGARY
Endrich Bauelemente Vertriebs GmbH office Budapest
URL http://www.endrich.com/
Mail hungary@endrich.com

SPAIN
Endrich Bauelemente Vertriebs GmbH office Barcelona
URL http://www.endrich.com/
Mail spain@endrich.com

ROMANIA
Endrich Bauelemente Vertriebs GmbH office Timisoara
URL http://www.endrich.com
Mail romania@endrich.com

BULGARIA
Endrich Bauelemente Vertriebs GmbH office Sofia
URL http://www.endrich.com/
Mail bulgaria@endrich.com



SWITZERLAND
Stolz Electronics AG
URL http://www.stolzelectronics.ch/
Mail info@stolzelectronics.ch

FINLAND
Oy Nylund-Group Ab
URL http://www.nylund.fi/
Mail nylund@nylund.fi

UNITED KINGDOM
Rhopoint Components, Ltd.
URL http://www.rhopointcomponents.com
Mail sales@rhopointcomponents.com

Profusion plc
URL http://www.profusionplc.com
Mail sales@profusion.email

Gateway Electronic Components Ltd.
URL http://www.gatewaycando.com
Mail sales@gatewaycando.com

RS Components K.K
URL http://uk.rs-online.com/web/

ISRAEL
BORAN TECHNOLOGIES LTD.
URL http://www.boran.co.il
Mail support@boran.co.il



SUSUMU CO., LTD.

JAPAN

SUSUMU CO., LTD. Headquarters

14 Umamawashi-Cho Kamitoba, Minami-Ku Kyoto, 601-8177 Japan

TEL +81-75-671-7371 FAX +81-75-671-7374 URL http://www.susumu.co.jp/ Mail : info@susumu.co.jp

http://www.susumu.co.jp/english/

GERMANY

SUSUMU DEUTSCHLAND GmbH

Frankfurter Strasse 63-69, 7th Floor, D-65760, Eschborn, Germany

TEL +49-6196-969-8407 FAX +49-6196-969-8879 URL http://www.susumu.de/ Mail : info@susumu.de

U.S.A

SUSUMU INTERNATIONAL(USA) INC. East Coast Office(H.Q.)

460 Bergen Blvd., Suite 226, Palisades Park, NJ, 07650, USA

TEL +1-201-461-4861 FAX +1-201-461-4862 URL http://www.susumu-usa.com/ Mail : info@susumu-usa.com

CHINA

SUSUMU INTERNATIONAL TRADING (SHANGHAI) CO., LTD.

Room422, 3U Building, 8 Huajing Road, Pilot Free Trade Zone, Shanghai City P.R.C, 200131

TEL +86-21-5046-4992 FAX +86-21-5046-4993 URL http://www.susumu.sh.cn/ Mail : susumu@susumu.sh.cn

SINGAPORE

SUSUMU SINGAPORE PTE.LTD.

629 Aljunied Road #03-20, Cititech Industrial Building, Singapore, 389838

TEL +65-6741-4070 FAX +65-6741-2971 URL http://www.susumu.sg/ Mail : ssm-sg@susumu.co.jp

This catalogue is current as of Mar, 2018.